



MASTER MHN-LA

MASTER MHN-LA 1000W/956 230V XWH

Compact quartz metal halide lamps with double-pin

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


Operating and Electrical		Controls and Dimming	
Power Consumption	1,040.0 W	Dimmable	No
Voltage (Nom)	125 V		
Voltage (Nom)	125 V		
General Information		Mechanical and Housing	
Cap-Base	X528 [X528]	Bulb Finish	Clear
Operating Position	P5 [Parallel +/-5D or Horizontal(HOR)]	Bulb Shape	TD40 [TD 40mm]
Light Technical		Approval and Application	
Color Code	956 [CCT of 5600K]	Mercury (Hg) Content (Nom)	95 mg
Color Designation	Daylight	Energy Consumption kWh/1000 h	1144 kWh
Chromaticity Coordinate X (Nom)	337		
Chromaticity Coordinate Y (Nom)	331		
Correlated Color Temperature (Nom)	5600 K		
Luminous Efficacy (rated) (Nom)	86.0 lm/W		
Color rendering index (CRI)	80		
Product Data			
Full product code	871150020077800		
Order product name	MASTER MHN-LA 1000W/956 230V XWH		
Order code	928072205130		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material number (12NC)	928072205130		
Full product name	MASTER MHN-LA 1000W/956 230V XWH		

MASTER MHN-LA

EAN/UPC - Case


8711500200778

Dimensional drawing




Product	D (max)	O	X	A
MASTER MHN-LA 1000W/956 230V XWH	40 mm	40.5 mm	35 mm	286 mm

Photometric data




Spectral Power Distribution Colour - MASTER MHN-LA 1000W/956 230V XWH

Lifetime



Life Expectancy Diagram - MASTER MHN-LA 1000W/956 230V XWH



Lumen Maintenance Diagram - MASTER MHN-LA 1000W/956 230V XWH

