

DIONE LED PLUS MULTI 1650-2610LM 830 IP65 I KL. OPAL WHITE 22W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK10
Nominal power [W] - range:	15/18/22/26
Colour temperature [K]:	3000
Luminous flux of the luminaire [lm] - range:	1650/1900/2300/2610
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS
Diffuser material:	PC

CHARACTERISTICS

Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells. Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor). The MULTI luminaire version allows individual configuration: thanks to the built-in micoswitch, it is possible to choose one of 4 settings (nominal power of the fitting [W] / luminous flux of the fitting [lm]).

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes) or outdoor. It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

DIONE LED PLUS MULTI 1650-2610LM 830 IP65 I KL. OPAL WHITE 22W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W] - range:	15/18/22/26	Ring material:	ABS
Index:	951800	Ring colour:	white
Colour temperature [K]:	3000	Dimensions (H/W/T/S) [mm]:	340x115
EAN:	5905963951800	Mounting dimensions [mm]:	140
Luminous flux of the luminaire [lm] - range:	1650/1900/2300/2610	Impact resistance:	IK10
Diffuser type:	OPAL	Ingress protection:	IP65
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Dimensions of single box [mm]:	340/340/115
Luminous efficacy [lm/W]:	103	Number on the palette [pcs]:	80
Energy efficiency class:	E	Permeability factor of the diffuser:	0.73
Electrical protection class:	I	Category type:	bulkheads
Colour rendering index:	>80	Category of application:	commercial facilities, educational institutions
SDCM:	≤ 3	LED lifespan L70B50 [h]:	110000
Power factor:	0.95	LED lifespan L80B20 [h]:	84000
Beam angle [°]:	120	LED lifespan L90B10 [h]:	33000
Diffuser material:	PC	Light distribution type:	open space
Diffuser colour:	white	Vandalproof:	yes
Material of the body:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	Warranty [years]:	5
		CE certificate:	379/2023
		PZH certificate:	B-BK-60212-0619/20
		Manual:	Download PDF
		Plik LDT:	Download

DIONE LED PLUS MULTI 1650-2610LM 830 IP65 I KL. OPAL WHITE 22W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
120DL118	Ceiling ring Dione LED steel 1.5 white matt RAL 9003 painted vandal resistant



Ceiling ring Dione LED steel 1.5 white
matt RAL 9003 painted vandal
resistant (120DL118)

Card creation date:10 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 379/2023