

CAPELLA LED PLUS EDGE BOX RING 1500LM 840 IP54 DALI BIAŁY (15W) 340MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	949647
Ingress protection:	IP54
Impact resistance:	IK07
Nominal power [W]:	15
Luminous flux [lm]*:	1500
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED PLUS EDGE BOX RING 1500LM 840 IP54 DALI BIAŁY (15W) 340MM

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Nominal power [W]:	15	Diffuser type:	OPAL
Light source:	LED module	Diffuser colour:	white
Colour temperature [K]:	4000	Optics material:	PMMA
Luminous flux [lm]:	1500	Optics:	lens
Rated power of the luminaire [W]:	16	Material of the body:	ABS
Supply voltage [V]:	220-240	Colour of the body:	white
Frequency [Hz]:	50 - 60	Ring material:	ABS
EDGE/BOX Colour:	white	Mounting dimensions [mm]:	158
Ring colour:	white	Impact resistance:	IK07
Version:	EDGE BOX RING	Ingress protection:	IP54
Luminous efficacy [lm/W]:	94	Mounting version:	surface
Energy efficiency class:	E	Working temperature [°C]:	from -10 to +35
Electrical protection class:	II	Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Colour rendering index:	>80	Dimensions of single box [mm]:	342/342/122
DIMM DALI:	yes	Net weight [kg]:	1.120
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.94	CE certificate:	373/2023
Dimensions (H/W/T/S) [mm]:	340/105	Index:	949647
LED lifespan L70B50 [h]:	115000	EAN:	5905963949647
Beam angle [°]:	120	Category type:	bulkheads
Surge protection [kV]:	1	Product line:	plus
Diffuser material:	PC	AC voltage range [V]:	220 - 240
		UGR (4H8H):	17,5-25,2
		Light distribution type:	lamertian
		Dimensions of bulk box (H/W/D) [mm]:	794/1194/982
		Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES

CAPELLA LED PLUS EDGE BOX RING 1500LM 840 IP54 DALI BIAŁY (15W) 340MM

DETAILED CARD



TECHNICAL DETAILS



CAPELLA LED EDGE

Card creation date: 17 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 373/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl