


MINGATA midi

612184.004.76 | Pole luminaires



Outdoor luminaires and pole top luminaires
4051859366775
L 700, B 340, H 100

Pole mounting
silver, matt (approx. RAL 9006)



Functional pole-side and pole-top luminaire in a modern design. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. Pole-top fixing with integrated cable routing and stainless steel screws. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass. Asymmetrical light distribution for area lighting (P or C lighting classes). Luminaires for pole top Ø 76 mm (with optional adapter sleeve, also suitable for pole top Ø 60 mm). Tool-free maintenance / replacement by Eccentric-Lock system with disconnect plug and Hybrid-Lock-System. 4 x 1.0 mm² connecting cable included, length 8 m.

Product specifications

Length L	700 mm
Width B	340 mm
Height H	100 mm
Weight	8 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	10000 lm
System power	66 W
System efficiency	152 lm/W
Glare evaluation UGR (4H 8H)	38,8
Beam angle	56°/67°/56°/0°
Rated life	100000 h (L80/B50)
Colour rendering index (CRI)	70
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	7
Luminaires on B16A fuse	11
Inrush current / Inrush current duration	65 A / 160 µs
CIE Flux Code / CEN Flux Code	34 74 98 100 100
Type of protection	IP 66
Protection class	II
Filament test	960 °C
Impact resistance	IK08
Ambient temperature	-20 °C ... + 50 °C
Conformity mark	CE, EAC

Accessories



982562.000
Reducing adapter Ø 60 mm



982588.000
Pole bracket for 2 luminaires, uncoated

MINGATA midi

612184.004.76 | Pole luminaires



982589.000
Pole bracket for 3 luminaires, uncoated



982590.000
Pole bracket for 4 luminaires, uncoated



982591.000
Wall bracket, uncoated



61199.009
Fuse box



982591.004
Wall bracket, powder-coated