

# PRODUCT DATASHEET

## LN INV D 1200 P 40W 930 PS WT

LINEAR INDIVILED DIRECT 1200 PS | Surface mounted luminaire for single or light line office application with CRI90 and power select (PS) feature, 1200 mm



### Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct lighting



### Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Homogenous light distribution and reduced glare ( $UGR \leq 19$ ) thanks to IndiviLED® optics
- High performance with CRI90 and up to 130 lm/W
- Highly versatile due to selectable power steps (Power Select - PS) on the driver
- Symmetric and asymmetric light distribution for various application areas
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Multiple mounting options thanks to different accessories

### Product features

- Minimalistic LEDVANCE SCALE design in extruded aluminum housing, available in white and black color
- Includes EVERLOOP: Convenient replacement of light source and LED driver
- Linkable into seamless light line with accessories (surface or pendant mounting)



- Pendant mounting with suspension kit (to be ordered separately)
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm<sup>2</sup>
- Lifetime (L80/B10): 70,000 h (at 25 °C)


## TECHNICAL DATA

### Electrical data


Nominal wattage	40 W / 36 W / 30 W / 25 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	185...170...140...120 mA
Inrush current	15 A
Inrush current time $T_{h50}$	50 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	50
Max. number of luminaires per miniature circuit breaker C10	36
Max. number of luminaires per miniature circuit breaker C16	58
Power factor $\lambda$	$\geq 0.90$
Total harmonic distortion	$\leq 20$ %
Protection class	I
Operating mode	Integrated LED driver

### Photometrical data

Luminous flux	4660 lm / 4270 lm / 3590 lm / 3060 lm
Luminous efficacy	120 lm/W / 122 lm/W / 123 lm/W / 126 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 90
Standard deviation of color matching	3 sdc <sub>m</sub>
Low flicker	Yes
Flickering metric (Pst LM)	$\leq 1$
Stroboscope effect metric (SVM)	$\leq 0.4$
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	90 °
UGR	< 19




LN INV D 1200 P 40W 930 PS WT 800mA



LN INV D 1200 P 40W 930 PS WT 800mA

Dimensions & Weight

Length	1210.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3200.00 g



LN INV 1200 P

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Adjustable	No
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	100000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	70000 h <sup>1)</sup>
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Control gear

Output current	800 mA
ECG - Output ripple current	≤ 5 %
Recommended control gear	OSRAM type IT FIT 40/220-240/800 CS L

### Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC / EPD
-----------	---


Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00027-V01.01-EN
Replaceable light source (EPREL)	By the end consumer

Additional product data

Number of illuminants	1
Added function	EVERLOOP / MULTI SELECT

Accessories Optional

Product image	Product name	EAN
	LN INV CORNER CONNECTOR WT	4099854214905
	LN INV SUSPENSION WIRE	4099854215551
	LN INV 1200 THROUGHWIRING KIT	4099854214820
	LN INV INFILL 1500 WT	4099854214844
	LN INV INFILL 600 WT	4099854214882
	LN INV INFILL 1200 WT	4099854214868
	LN INV INLINE CONNECTOR	4099854215612

Product image	Product name	EAN
	LN INV SUSPENSION KIT WT	4099854215537







### EQUIPMENT / ACCESSORIES



- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available









### Safety advice

- All electrical connections must be made by a qualified person.
- If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by a qualified person in order to avoid a hazard.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	LN INV
 Legal information	LN INV PS
 Legal information	LSI LN INDIVLED
 Legal information	Legal Insert LN INV P PS
 Legal information	Informationstext 18 Abs 4 ElektroG
 Declarations of conformity	LN INV

Photometric and lighting design files	Document name
 IES file (IES)	LN INV D 1200 P 40W 930 PS WT 800mA
 LDT file (Eulumdat)	LN INV D 1200 P 40W 930 PS WT 800mA

Photometric and lighting design files		Document name
	ULD file (DIALux)	LN INV D 1200 P 40W 930 PS WT
	ROLF file (RELUX)	LN INV D 1200 P 40W 930 PS WT
	UGR file (UGR table)	LN INV D 1200 P 40W 930 PS WT 800mA
	Light distribution curve type cone	LN INV D 1200 P 40W 930 PS WT 800mA
	Light distribution curve type polar	LN INV D 1200 P 40W 930 PS WT 800mA
CAD/BIM files		Document name
	BIM Revit 3D	Linear Indiviled G2
	CAD STEP 3D	LN INV D 1200 G2
Tender texts		Document name
	Tender documents	LINEAR INDIVILED DIRECT 1200 PS 1200 P 40W 930 PS WT-EN


**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854135316	Folding box 1	178 mm x 1,263 mm x 103 mm	3800.00 g	23.16 dm <sup>3</sup>
4099854135323	Shipping box 2	1,277 mm x 187 mm x 189 mm	9000.00 g	45.13 dm <sup>3</sup>


The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**ADDITIONAL CATALOG INFORMATION**







LINEAR IndivLED <sup>®</sup> DIRECT WT		DRIVER		40 mA/PCS		Presel	mA	W	lm	lm/W
LN INV D 1200 P 40W 930 PS WT	CSRAM	OFF	OFF	-	800	25	3750	126		
	ET-FF-40	ON	ON	-	800	25	3750	126		
LN INV D 1200 P 40W 930 PS WT	CSRAM	OFF	OFF	-	700	38	4500	120		
	ET-FF-40	ON	ON	Presel	800	42	4800	120		
LN INV D 1200 P 40W 940 PS WT	CSRAM	OFF	OFF	-	800	25	3750	126		
	ET-FF-40	ON	ON	-	800	25	3750	126		
LN INV D 1200 P 40W 940 PS WT	CSRAM	OFF	OFF	-	700	38	4500	120		
	ET-FF-40	ON	ON	Presel	800	42	4800	120		
LN INV D 1500 P 32W 930 PS WT	CSRAM	OFF	OFF	-	800	40	4800	121		
	ET-FF-40	ON	ON	-	800	40	4800	121		
LN INV D 1500 P 32W 930 PS WT	CSRAM	OFF	OFF	-	575	48	3600	118		
	ET-FF-40	ON	ON	Presel	1000	52	5800	118		
LN INV D 1500 P 32W 940 PS WT	CSRAM	OFF	OFF	-	800	40	4800	121		
	ET-FF-40	ON	ON	-	800	40	4800	121		
LN INV D 1500 P 32W 940 PS WT	CSRAM	OFF	OFF	-	575	48	3600	118		
	ET-FF-40	ON	ON	Presel	1000	52	5800	118		



LINEAR IndivLED <sup>®</sup> DIRECT		DRIVER		40 mA/PCS		Presel	mA	W	lm	lm/W
LN INV D 1200 P 40W 930 PS WT	CSRAM	OFF	OFF	-	800	25	3750	126		
	ET-FF-40	ON	ON	-	800	25	3750	126		
LN INV D 1200 P 40W 930 PS WT	CSRAM	OFF	OFF	-	700	38	4500	120		
	ET-FF-40	ON	ON	Presel	800	42	4800	120		
LN INV D 1200 P 40W 940 PS WT	CSRAM	OFF	OFF	-	800	25	3750	126		
	ET-FF-40	ON	ON	-	800	25	3750	126		
LN INV D 1200 P 40W 940 PS WT	CSRAM	OFF	OFF	-	700	38	4500	120		
	ET-FF-40	ON	ON	Presel	800	42	4800	120		
LN INV D 1500 P 32W 930 PS WT	CSRAM	OFF	OFF	-	800	40	4800	121		
	ET-FF-40	ON	ON	-	800	40	4800	121		
LN INV D 1500 P 32W 930 PS WT	CSRAM	OFF	OFF	-	575	48	3600	118		
	ET-FF-40	ON	ON	Presel	1000	52	5800	118		
LN INV D 1500 P 32W 940 PS WT	CSRAM	OFF	OFF	-	800	40	4800	121		
	ET-FF-40	ON	ON	-	800	40	4800	121		
LN INV D 1500 P 32W 940 PS WT	CSRAM	OFF	OFF	-	575	48	3600	118		
	ET-FF-40	ON	ON	Presel	1000	52	5800	118		



References / Links

- For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.