



IN STAT+ 2R



IN STAT+ 3R




IN STAT+ 3F


### Varianten | Variations

| Bestellbez.   Type   | INSTAT+ 2R   | INSTAT+ 3R                                    | INSTAT+ 3F**   |
|--|--|---|--|
| Artikel-Nr.   Article No.  | 0537 10 291 900  | 0537 20 141 900                               | 0537 30 141 900  |
| <b>Raumregler</b><br>Room temperature controller<br>Temp. 7...32 °C        | ●  | ●   |  |
| <b>Fußbodenregler</b><br>Underfloor heating controller<br>Temp. 10...40 °C |  |   | ●  |
| Betriebsspannung<br>Supply voltage   | Batterie: 2 x 1,5 V (AA),<br>Lebensdauer ≥ 3 Jahre<br>Battery: 2 x 1,5 V (AA),<br>Service life ≥ 3 years | Netz; AC 230V, 50 Hz<br>mains; AC 230V, 50 Hz | Netz; AC 230V, 50 Hz<br>mains; AC 230V, 50 Hz  |
| Fernfühler<br>Remote sensor  | –  | –   | im Lieferumfang enthalten<br>F 193 720, Länge 4 m,<br>verlängerbar auf 50 m<br>included in delivery<br>F 193 720, length 4 m,<br>extendable up to 50 m |
| Fühlerüberwachung<br>Sensor monitoring                                     | –  | –   | 30% Heizen bei Fühlerfehler<br>30% heating when sensor error   |

### Schaltzeichnung | Wiring diagram



INSTAT+ 2R



INSTAT+ 3R, 3F