

PRODUCT-DETAILS

# A43 212-100

## A43 212-100, Energy meter 'Bronze', Modbus RS485, Three-phase, 80 A



### General Information

Extended Product Type	A43 212-100
Product ID	2CMA170522R1000
ABB Type Designation	A43 212-100
EAN	7392696705226
Catalog Description	A43 212-100, Energy meter 'Bronze', Modbus RS485, Three-phase, 80 A

Long Description

Advanced DIN-rail meter with a large and easy to read back lighted pixel-oriented display. The meter is intended for use in the industry, commercial buildings etc. The meter can be used in 3 or 4 wire systems with a wide voltage range. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase direct connected for active and reactive energy. Import and export of energy in different registers and one total. One output for pulses or alarm etc. RS-485 communication over Modbus RTU or EQ Bus. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.

### Eco Transparency

Environmental Product Declaration - EPD	9AKK108467A4138
---	-----------------

### Technical

Standards	IEC 62052-11
Function	Electricity meter

Sub-Function	Bronze
Rated Voltage (U <sub>r</sub> )	3x57.7-288 V
Rated Current (I <sub>n</sub> )	5 A Maximum 80 A
Current Rating	80 A
Rated Frequency (f)	50 / 60 Hz
	0.807 W
Communication Interface	Modbus RS485
Accuracy	Active Energy Class B MID (±1%)
Measuring Instrument Conformity	Measurement Instrument Directive (MID)
Meter Tariff Rating	One-Tariff
Pulse Output Rate	1-999999
Number of Poles	4
Number of Phases	Three-phase
Number of Counter Positions	7
Number of Digital In/Outputs	1 DO
Meter Type	Direct connected
Mounting Type	DIN-Rail
Pulse Output Type	Electrical
Type of Indicator	Digital
Enclosure Material	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.
Connecting Capacity Main Circuit	1 ... 25 mm <sup>2</sup>

## Environmental

Ambient Air Temperature	Operation -40 ... 70 °C
Degree of Protection	IP20
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Information	2CMC484006
Environmental Information	2CMC484004D0001
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Width in Number of Modular Spacings	7
Product Net Width	123 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.448 kg
Size	97X123X65

## Ordering

Minimum Order Quantity	1 piece
Package Level 1 Units	box 1 piece

Package Level 1 Gross Weight	0.538 kg
E-Number (Finland)	6625007
E-Number (Sweden)	0980704

## Certificates and Declarations

Declaration of Conformity - CE	2CMC484003D0001
--------------------------------	-----------------

## Installation

Instructions and Manuals	2CMC484003M0201
--------------------------	-----------------

## Popular Downloads

Data Sheet, Technical Information	2CMC484001M0201
-----------------------------------	-----------------

## Classifications

ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283019
eClass	V11.0 : 27142316
Object Classification Code	P

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1 Energy Analyzer, M-Bus, 16 Devices, MDRC	QA/S3.16.1	1	piece
2CDG110227R0011	QA/S3.64.1 Energy Analyzer, M-Bus, 64 Devices, MDRC	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Energy Efficiency Devices → Energy Meters

