


FLAT POLYMERO

672335.002.4 | Combined luminaires for escape route illumination



Ceiling and wall luminaires
4051859718628
D 360, H 100

Ceiling mounting, Wall (surface)
white



Decorative round surface-mounted luminaire. For escape route illumination. Base: metal, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for Ceiling mounting, Wall (surface). Driver integrated.

Product specifications

Typ of emergency lighting	Central battery system
Monitoring	Power circuit
Battery	without
Operating mode	maintained power mode
Diameter D	360 mm
Height H	100 mm
Weight	1.28 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux, mains operation	1350 lm
System power, mains operation	13 W
Rated luminous flux, emergency operation	340 lm
System power, emergency operation	2,7 W
System efficiency	104 lm/W
Glare evaluation UGR (4H 8H)	19,5
Beam angle	down 111° up 180°
Colour rendering index (CRI)	80
Photobiological safety according to EN 62471	Risk group 1
Driver	Not necessary
Control	on/off
Voltage	220 - 240 V / 0 Hz, 50 Hz, 60 Hz
CIE Flux Code / CEN Flux Code	44 74 91 93 100
Type of protection	IP 40
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK10
Ambient temperature for maintained power	-15 °C ... + 35 °C
Ambient temperature for non-maintained power mode	-15 °C ... + 35 °C
Conformity mark	CE