

Ceasr Opera, walk over

96701751 CESAR OPERA M WO 2L 930 NB RD ANT

THORN

LED 6W CESA_OP_M_NB_930	IP67	IK09			
-------------------------	------	------	---	---	--


Ceasr Opera, walk over

Ceasr Opera, walk over a floor recessed, architectural LED luminaire for decorative facade lighting, narrow beam distribution. DALI-2 dimmable Remote LED driver. Class III electrical, IP67, Impact strength: IK09. Housing: die-cast aluminium, powder coated anthracite. Working ambient temperature: -20°C to +50°C. Complete with 3000K LED.


Dimensions: Ø165 x 135 mm
Luminaire input power: 5.6 W
Luminaire luminous flux: 304 lm
Luminaire efficacy: 54 lm/W
Weight: 1.42 kg



TLG_CESA_F_OPERA_M_WO_NB_ANT.jpg



TLG_CESA_M_OPERA_M_WO.wmf



96701751.ltd

Lamp position: STD - standard
Light Source: LED
Luminaire luminous flux*: 304 lm
Luminaire efficacy*: 54 lm/W
Colour Rendering Index min.: 90
Correlated colour temperature*: 3000 Kelvin

Chromaticity tolerance (initial MacAdam): 3
Rated useful life (B10)*:
L80 70000 h at 25 °C
Ballast: 0x LED_DRV
Luminaire input power*: 5.6 W
Dimming: Dali2Dim
LOR: 0,99 ULOR: 0,99 DLOR: 0,00

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting