


TRIONA rectangle

312729.0031.76 | Pendant luminaires



Pendant luminaires
4051859968108
L 1560, B 350, H 52

pendant
anthracite metallic (DB703)



Decorative rectangular LED pendant area luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Canopy made of aluminium, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. LED backlight technology for homogeneous illumination of the entire light-emitting surface. 2-point steel cable suspension, steplessly adjustable. Easy installation with transparent, adjustable pendant cable and canopy with magnetic fixing. Driver integrated. Dimmable DALI. Suitable for through-wiring.

Product specifications

Length L	1560 mm
Width B	350 mm
Height H	52 mm
Suspension length LP	1200 mm
Weight	15 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	12200 lm
System power	101 W
System efficiency	121 lm/W
Glare evaluation UGR (4H 8H)	23,8
Beam angle	109°/107°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	12
Luminaires on B16A fuse	20
Luminaires on C10A fuse	21
Luminaires on C16A fuse	33
Inrush current / Inrush current duration	20 A / 200 µs
CIE Flux Code / CEN Flux Code	48 79 96 100 100
Type of protection	IP 20
Protection class	I
Filament test	650 °C
Impact resistance	IK03
Ambient temperature	-20 °C ... + 35 °C
Conformity mark	CE