

# PIATTO SUSPENDED FI 340MM 520LM I KL. BLACK-GOLD IP20 830 (9W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                          |                         |
|--------------------------|-------------------------|
| Index:                   | 654060                  |
| Ingress protection:      | IP20                    |
| Nominal power [W]:       | 9                       |
| Luminous flux [lm]*:     | 520                     |
| Colour temperature [K]:  | 3000                    |
| Colour rendering index:  | >80                     |
| Energy efficiency class: | G                       |
| Material of the body:    | powder coated aluminium |
| Colour of the body:      | black-gold              |
| Diffuser material:       | PC                      |

## CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. The integrated energy-saving LED GO! panel ensures high light quality and long-term trouble-free use.

## APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.

# PIATTO SUSPENDED FI 340MM 520LM I KL. BLACK-GOLD

## IP20 830 (9W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

|                                   |            |
|-----------------------------------|------------|
| Nominal power [W]:                | 9          |
| Rated power of the luminaire [W]: | 9.30       |
| Colour temperature [K]:           | 3000       |
| Luminous flux [lm]:               | 520        |
| Colour of the body:               | black-gold |
| Energy efficiency class:          | G          |
| Light source:                     | LED module |
| Supply voltage [V]:               | 220-240    |
| Frequency [Hz]:                   | 50 - 60    |
| Luminous efficacy [lm/W]:         | 55         |
| Electrical protection class:      | I          |
| Colour rendering index:           | >80        |
| Power factor:                     | 0.53       |
| Diffuser material:                | PC         |
| Diffuser type:                    | OPAL       |

|                            |                              |
|----------------------------|------------------------------|
| Material of the body:      | powder coated aluminium      |
| Dimensions (H/W/T/S) [mm]: | ø340/280/1500                |
| Ingress protection:        | IP20                         |
| Mounting version:          | suspended                    |
| Working temperature [°C]:  | from -25 to +25              |
| Net weight [kg]:           | 2.300                        |
| CE certificate:            | <a href="#">221/2023</a>     |
| Index:                     | 654060                       |
| EAN:                       | 5905963654060                |
| Category type:             | architectural, downlights    |
| Cable length [m]:          | 1.50                         |
| ETIM class:                | EC001743                     |
| Manual:                    | <a href="#">Download PDF</a> |
| Plik LDT:                  | <a href="#">Download</a>     |

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 221/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)