

WALL PLUS

WALL-MOUNTED EFFECT LIGHT | 1 WIDE BEAM

STL22733PTO/30



5W


Power

260lm

Luminous flux

90°


Beam angle




TECHNICAL SPECIFICATIONS TABLE

|                                    |            |
|------------------------------------|------------|
| Beam angle                         | 90°        |
| Power factor                       | 0,92       |
| Luminous flux                      | 260lm      |
| Frequency                          | 50/60Hz    |
| Ingress protection rating (IP)     | IP65       |
| CRI (Color rendering index)        | 80         |
| Power                              | 5W         |
| Correlated color temperature (CCT) | 3000K      |
| Voltage (V)                        | 100-240V   |
| Voltage (Vac)                      | 100-240Vac |
| Lifespan                           | 25000h     |

Technical Drawing



Graphics



OTHER INFORMATION

|                     |                  |
|---------------------|------------------|
| Finishing           | Black            |
| Color temperature   | Warm white       |
| Dimmable            | No               |
| Warranty            | 2 years          |
| Patent information  | Patented product |
| Prevailing material | Polycarbonate    |

DOWNLOADS

↓ IES FILE - STL22733PTO/30

↓ MANUAL Wall Plus

↓ SKETCHUP - STELLA - STL22733BR-30 - STL22733PTO-30 - WALL PLUS\_PACK.zip

↓ REVIT - STL22733BR\_PTO\_30.rfa

