

Junction box

Abox SL-10²



Abox SL-10²

Junction box

Productnumber: 81044001

Dimensions: 182 x 182 x 90 mm

Junction box, protection class IP55/IP66, nominal cross-section 10 mm², Ui=690 V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), DLG (Ammonia resistance), knockouts, M20/M32/M40, (2 rear, 10 side), internal fixing points, with screwless terminals for standard indoor and protected outdoor installations

grey, In=57 A, with raised screwless terminal block Wago 2010-1201, 5-pole, max. nominal cross-section in accordance with DIN EN 60998: 10 mm², clampable cross-sections per pole: 4 x 0.5 to 16 mm² rigid/flexible Cu

Accessories supplied:

4 attachment bushes IP55 M40 sealing range 17 - 30 mm, 1 sealing plug IP55 M40, cover retainer



Technical Data

electrical characteristics

Rated insulation voltage AC:	690 V
Rated insulation voltage DC:	690 V
Min. conductor cross section:	0,5 mm²
Max. conductor cross section:	10 mm²
Protection class:	II
Type of protection:	IP55/IP66
Rated current:	57 A
Terminal type:	screwless
Number of poles:	5

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	182 mm
Length:	182 mm
Height:	90 mm
Inner length:	167 mm
Inner width:	167 mm
Inner height:	69 mm
Weight:	0.8764 kg

Material characteristics

UV-resistant:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	750 °C

mechanical properties

Impact strength:	IK07
Sealable:	yes
Cover screw torque:	1.5 Nm
Type of fastening:	Wall/ceiling mounting
Fastening:	internal fixing points

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	55 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902660421
Packing Unit Code:	C62
ETIM Class:	EC002600
Custom tariff number:	85369095

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Thermoplastic elastomer
Cover screw material:	Stainless steel V2A

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
Test mark:	DLG (Ammonia resistance)

Accessories

[89600701 - Abox 160 KH 2010 10² - Terminal holder](#)

[22742101 - KVR M20-GDB/MGM - Cable gland](#)

[22742001 - KVR M20-MGM - Cable gland](#)

[22743201 - KVR M32-MGM - Cable gland](#)

[22744001 - KVR M40-MGM - Cable gland](#)

[26042001 - DMS M20 - Double-membrane seals](#)

[26043201 - DMS M32 - Double-membrane seals](#)

[26044001 - DMS M40 - Double-membrane seals](#)

[23042001 - AST M20 - Attachment bushes](#)

[23043201 - AST M32 - Attachment bushes](#)

[23044001 - AST M40 - Attachment bushes](#)

[89603001 - MABF 150-1 - Mast/pipe fixing set](#)

[89600901 - KTB 1 - Fastening parts kit](#)

Cable gland

