

OVAL LED EVO HV 170MM 530LM 830 S.METAL ROZKŁ. POPIEL KLOSZ SZKLANY (5W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	911200
Ingress protection:	IP44
Impact resistance:	IK06
Nominal power [W]:	5
Luminous flux [lm]*:	530
Colour temperature [K]:	3000
SDCM:	≤ 4
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	glass

CHARACTERISTICS

Surface mounted, LED luminaire, with an integrated energy-efficient LED GO! panel that provides high luminous efficacy and high ingress protection class of IP44 (wall assembly) and IP40 (ceiling assembly). The base is made of polypropylene and the diffuser is made of glass or polycarbonate. Characteristics: color temperature 3000K, 4000K; CRI> 80; durability of LED panels 50,000 hours (L70B50) ta = 25 ° C

APPLICATION

Surface mounted luminaire with plastic or metal grid for mounting on ceilings and walls; intended for indoor use (rooms with high humidity, passageways and staircases, sewers and basements) as well as outdoor use (industrial facade lighting, parking lots).

OVAL LED EVO HV 170MM 530LM 830 S.METAL ROZKŁ. POPIEL KLOSZ SZKLANY (5W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	5	Dimensions (H/W/T/S) [mm]:	170/125/115
Light source:	LED module	Mounting dimensions [mm]:	110
Colour temperature [K]:	3000	Impact resistance:	IK06
Luminous flux [lm]:	530	Ingress protection:	IP44
Rated power of the luminaire [W]:	6.10	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from 0 to +25
Diffuser type:	PRM	Net weight [kg]:	0.390
Frequency [Hz]:	50 - 60	CE certificate:	402/2023
Colour of the body:	gray	Index:	911200
Luminous efficacy [lm/W]:	87	EAN:	5905963911200
Energy efficiency class:	F	Category type:	bulkheads
Electrical protection class:	I	Category of application:	parkings and bicycle paths
Colour rendering index:	>80	Version:	metal, demountable grid
SDCM:	≤ 4	Luminaire rated power 0min [W]:	6.10
Power factor:	0.99	ETIM class:	EC001058
LED lifespan L70B50 [h]:	80 000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	120	Warranty [years]:	3
Diffuser material:	glass	Manual:	Download PDF
Material of the body:	PP		

Card creation date:10 January 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 402/2023