
HELEDON mini


901749.003 | Recessed downlights





Recessed downlights 4051859844204 D 124, H 3

Recessed ceiling mounting deep black, matt (RAL 9005)



Round recessed downlight. Housing: die-cast aluminium, powder-coated. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. Suitable for Recessed ceiling mounting. Installation without tools thanks to spring fastening system. Including separate LED converter with connecting cable 600 mm. High quality converter without flickering and stroboscopic effect. Throughwiring box (5 pole) available as accessory. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.

Product specifications

| Froduct specifications | |
|--|--------------------------------------|
| Diameter D | 124 mm |
| Height H | 3 mm |
| Cut-out diameter DA | 114 mm |
| Luminaire: recess height HEL | 120 mm |
| Ceiling thickness S | 1-20 mm |
| Installation space length LE | 550 mm |
| Installation space width BE | 350 mm |
| Installation space height HE | 170 mm |
| Weight | 600 g |
| Light source | LED |
| Colour temperature | 3000 K |
| Rated luminous flux | 3500 lm |
| System power | 29 W |
| System efficiency | 121 lm/W |
| Glare evaluation UGR (4H 8H) | 15,6 |
| Beam angle | 31° |
| Rated life | 50000 h (L90/B10) |
| Colour rendering index (CRI) | 92 |
| Colour tolerance | 2 |
| Photobiological safety according to EN 62471 | Risk group 1 |
| Driver | Converter |
| Control | on/off |
| Voltage | 220 - 240 V / 50 Hz, 60 Hz |
| Luminaires on B10A fuse | 21 |
| Luminaires on B16A fuse | 34 |
| Luminaires on C10A fuse | 35 |
| Luminaires on C16A fuse | 57 |
| Inrush current / Inrush current duration | 11.1 A / 250 μs |
| CIE Flux Code / CEN Flux Code | 99 100 100 100 100 |
| Type of protection | IP 20 |
| Protection class | II |
| Filament test | 650 °C |
| Impact resistance | IK06 |
| Ambient temperature | -20 °C + 25 °C |
| Safety marks | Do not cover the recessed luminaire! |
| Conformity mark | CE, EAC |
| | |

HELEDON mini

901749.003 | Recessed downlights



Accessories



982370.000 Diffuser, transparent



982371.003 Anti-glare honeycomb louvre



982369.013 Medium lens



982421.002 White plastic ring for lens.



982368.013 Reflector medium



982369.033 Wide flood lens



982419.002 White plastic ring for reflector.



982647.002 Decorative glass opal matt



982703.002 Through-wiring box



982370.010 Diffuser, satinated



982369.003 Spot lens



982369.023 Flood lens



982368.003 Reflector spot



982368.023 Reflector flood



982369.043 Oval corridor lens



982368.033 Reflector wide flood



982648.002 Decorative glass opal matt