


BCO MOD ML2 B 180 (927 010)


- LifeCheck arrester monitoring and integrated status indication
- Two-pole protection module for lightning equipotential bonding
- For installation in conformity with the lightning protection zone concept at the boundaries from $0_A -1$ and higher



Figure without obligation



Basic circuit diagram BCO MOD ML2 B 180



Dimension drawing BCO MOD ML2 B 180

Protection module with a width of 6 mm for BLITZDUCTORconnect lightning current arrester with status indication for protecting two single lines for lightning equipotential bonding as well as indirect earthing of shielded cables.

Type	BCO MOD ML2 B 180
Part No.	927 010
SPD class	TYPE1
Impulse category	D1, C2, C3
Nominal voltage (U_N)	180 V
Max. continuous operating voltage (d.c.) (U_C)	180 V
Max. continuous operating voltage (a.c.) (U_C)	127 V
Nominal current (I_N)	1.2 A
D1 Total lightning impulse current (10/350 μ s) (I_{imp})	3 kA
D1 Lightning impulse current (10/350 μ s) per line (I_{imp})	1.5 kA
C2 Total nominal discharge current (8/20 μ s) (I_n)	10 kA
C2 Nominal discharge current (8/20 μ s) per line (I_n)	5 kA
Voltage protection level line-line for I_n C2 (U_p)	≤ 1100 V
Voltage protection level line-PG for I_n C2 (U_p)	≤ 800 V
Voltage protection level line-line at 1 kV/ μ s C3 (U_p)	≤ 950 V
Voltage protection level line-PG at 1 kV/ μ s C3 (U_p)	≤ 700 V
Series resistance per line	0 ohm(s)
Cut-off frequency line-line at 100 ohms (f_G)	150 MHz
Capacitance line-line (C)	≤ 10 pF pF
Capacitance line-PG (C)	≤ 13 pF pF
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Degree of protection (with plugged-in protection module)	IP 20
Plugs into	BCO base part
Earthing via	BCO base part
Enclosure material	polyamide PA 6.6
Colour	yellow
Test standards	IEC 61643-21 / EN 61643-21
Approvals	UL, CSA, EAC, ATEX, IECEx, CCC, SIL
ATEX approvals	TÜV 20 ATEX 8527 X: II 3G Ex ec IIC T4 Gc
IECEx approvals	IECEx TUR 20.0063X: Ex ec IIC T4 Gc
China Compulsory Certification	CCC no. 2021312304001192
Extended technical data:	-----
- Discharge current (8/20 μ s) [1/2 - PG], [1+2 - PG]	10 kA (10x)
- Voltage protection level line-PG at 1 kV/ μ s C3 after being subjected to I_{max} (U_p)	≤ 700 V
Weight	14 g
Customs tariff number	85363010
GTIN	4013364410114
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.