

PRODUCT DATASHEET

Flex Audio Voice Receiver 3M RGB + RC

FLEX AUDIO WITH REMOTE CONTROL | Decorative LED Strips with warm white light and RGB for indoor use, with sound receiver and remote control



Areas of application

- Living areas
- Indirect and direct lighting

Product benefits

- Easy and quick installation

Product features

- RGB color control
- Light color: Warm White
- With help of integrated voice-receivers the luminaire reacts to sound and music
- Flexible, bendable LED strips



TECHNICAL DATA

Electrical data

Nominal wattage	12.50 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	78.000 mA
Inrush current	28 mA
Power factor λ	> 0.5
Total harmonic distortion	< 100 %
Protection class	II

Photometrical data

Luminous efficacy	10 lm/W
Light color (designation)	Red / Green / Blue
Photobiological safety group acc. to EN62778	RG1
Beam angle	120 °

Dimensions & Weight

Length	3000.00 mm
Width	10.00 mm
Height	3.00 mm
Product weight	200.00 g

FLEX AUDIO 3M RGB VR RC

Materials & Colors

Product color	White
Housing color	White
Body material	Polyurethane (PU)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Temperature range at storage	-20...80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	Yes
Mounting type	Surface
Application environment	Indoor

Lifespan

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
Number of switching cycles	10000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

Battery size [GMS]	CR2025
--------------------	--------

Certificates & Standards

Standards	CE
Replaceable light source (EPREL)	Not replaceable




EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- Remote control and battery included

Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.
- Do not connect the rope light to the supply while it is wound onto a reel. Do not use the lightstrip when covered or recessed into a surface. The string of lights may not be operated within the packaging. Do not open the lightstrip.
- Battery Warning: Keep out of reach for children. Swallowing can lead to chemical burns, perforation of soft tissue, and death. Severe burns can occur within 2 hours of ingestion. Seek medical attention immediately.
- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	UI FLEX AUDIO RGB
 Legal information	Legal Insert FLEX
 Declarations of conformity	CE Declaration Flex COB and Audio

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854095382	Folding box 1	52 mm x 157 mm x 128 mm	244.00 g	1.04 dm ³
4099854095399	Shipping box 8	340 mm x 230 mm x 160 mm	2280.00 g	12.51 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.