

Terminal block enclosure

## RKKi 4/12-12x4<sup>2</sup>



### RKKi 4/12-12x4<sup>2</sup>

Terminal block enclosure

CUSTOMIZABLE

Productnumber: 63040401

Dimensions: 110 x 110 x 66 mm

Terminal block enclosure, with protection class IP54/IP66, Nominal cross-section 4 mm<sup>2</sup>, Ui=400V AC, Polycarbonate, Internal fastening points, for installations in the industrial arena and protected outside areas

**equipped with 12-pole terminal block 4mm<sup>2</sup>  
(Contaclip BKA 4 type)**

**Accessories supplied:**

**4 attachment bushes IP54 M20 seal range 8 -  
13,5 mm**



## Technical Data

### electrical characteristics

Rated insulation voltage AC:	400 V
Max. conductor cross section:	4 mm <sup>2</sup>
Protection class:	II
Type of protection:	IP54/IP66
UL Type Rating:	not specified

### Dimensions

Width:	110 mm
Length:	110 mm
Height:	66 mm

### Material characteristics

suitable for exterior use:	yes
Industry quality:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability according to EN 60695-2-11:	960 °C

### mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK08
Sealable:	yes
Stackable:	yes

### Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C

### Ambient conditions

24h ambient temperature:	35 °C
--------------------------	-------

### Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

## Accessories

[19000101 - HBA - Mounting material](#)

[19000201 - ASS-kl - External hinge set](#)

[19202001 - KS M20 - Combi set](#)

[19202501 - KS M25 - Combi set](#)

[19202601 - KS M25-gro - Combi set](#)

[19400101 - TK ABL - External fixing lugs kit](#)

## Cable gland

