

S.GROUND

LED INGROUND WITH ANTI-GLARE GRID

STL23717/30



6,5W

Power

360lm

Luminous flux

14°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Lifespan	25000h
Voltage (Vac)	100-240Vac
Voltage (V)	100-240V
Correlated color temperature (CCT)	3000K
Power	6,5W
Luminous intensity	3200cd
CRI (Color rendering index)	80
Ingress protection rating (IP)	IP67
Frequency	50/60Hz
Luminous flux	360lm
Power factor	0,92
Luminous efficacy	55lm/W
Beam angle	14°

Technical Drawing

STL23717



OTHER INFORMATION

Prevailing material	Aluminum
Patent information	Patented product
Warranty	2 years
Dimmable	No
Color temperature	Warm white
Finishing	Black


Graphics

STL23717

1m	2926lx	0,3m
2m	731lx	0,6m
3m	325lx	0,9m
4m	183lx	1,2m
5m	117lx	1,6m

h, Emax, Ø

STL23717



C0/180 C90/270

DOWNLOADS

[↓ IES FILE - STL23717/30](#)[↓ MANUAL S.Ground](#)[↓ SKETCHUP - STELLA - STL23717-30 - EMBUTIDO DE SOLO GROUND 6W COM GRADE_PACK.zip](#)[↓ REVIT - STL23717_30 - 5°.rfa](#)