

PRODUCT DATASHEET

Office Line Desk Banker Inductive Charging 17W CCT Dimmable White

Office Line Desk Banker Inductive Charging | Desk luminaire with inductive charging and 3-step dimming and color temperature adjustment function



Areas of application

- Living areas
- Tables, Desks
- Home offices

Product benefits

- Inductive charging area on the base
- Highly versatile due to selectable CCT
- Provides cold white light for an activating and warm white light for a relaxing atmosphere
- Switching and three step dimming via a touch sensitive sensor on the luminaire base
- Swivable luminaire head for individual orientation of light source
- Made of high quality aluminum

Product features

- Desk luminaire in timeless design and with adjustable luminaire head
- Adjustable light color: 3000 K, 4000 K, 6500 K
- Material: Aluminium (Housing), Polycarbonate (Diffusor)
- Lifetime up to 25,000 h



TECHNICAL DATA

Electrical data


Nominal wattage	17 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	92 mA
Inrush current	3.0 A
Inrush current time T_{h50}	100 μ s
Power factor λ	> 0.7
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	651 lm
Total luminous flux of contained light sources	780 lm
Luminous efficacy	38 lm/W
Color temperature	3000 K / 4000 K / 6500 K
Reference control setting of contained light source (Kelvin)	3000 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdc _m
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	113 °

Dimensions & Weight

Length	121.0 mm
Width	310.00 mm
Height	374.00 mm
Product weight	1062.00 g
Cable length	1800 mm



OFFICE LINE DESK BANKER 17W
CCT D IC

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminium Acrylonitrile butadiene styrene (ABS)
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Temperature range at storage	-20...+80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	Yes
Type of dimming	PWM
Mounting type	Standing
Application environment	Indoor
Adjustable	Yes
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / EAC
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from January 2025
----------------	-----------------------------




EQUIPMENT / ACCESSORIES

- Equipped with 1.8 m cable and plug

Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	
 Legal information	Legal insert residential luminaires
 Declarations of conformity	OFFICE LINE DESK BANKER ROOF

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075843004	Folding box 1	137 mm x 247 mm x 408 mm	1248.00 g	13.81 dm ³
4058075843011	Shipping box 8	564 mm x 510 mm x 435 mm	11578.00 g	125.12 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.