


TX-MOVE

901729.002.3 | Recessed projectors



Recessed projectors
4051859973553
L 622, B 116, H 39

Lay-in luminaires
traffic white, matt (RAL 9016)



Einlege/Einbau-Flächenstrahler. Housing: sheet steel, powder-coated. Swivel range: 90°. High-efficiency LED units with optimum light control thanks to clear plastic (PC) lens optics. Spezielle Mikrostrukturen reduzieren Gelbsaum. Symmetrical light distribution. Suitable for laying in grid ceiling module 625. Connected converter included in separate gearbox. Suitable for through-wiring. MultiLumen: Luminous flux adjustable in 3 steps. Accessories: Mounting frame for installation in suspended ceilings. Environmentally friendly and resource-saving due to replaceable and recyclable components.

Product specifications

Length L	622 mm
Width B	116 mm
Height H	39 mm
Cut-out length LA	602 mm
Cut-out width BA	98 mm
Installation space length LE	700 mm
Installation space width BE	316 mm
Installation space height HE	100 mm
Weight	2.15 kg
Light source	LED
Colour temperature	3500 K
Rated luminous flux	2950 lm 4050 lm 5700lm
System power	18 W 26 W 39W
System efficiency	146 lm/W 156 lm/W 164lm/W
Glare evaluation UGR (4H 8H)	21,4 22,5 23,7
Beam angle	85°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	21
Luminaires on B16A fuse	34
Luminaires on C10A fuse	35
Luminaires on C16A fuse	57
Inrush current / Inrush current duration	4.5 A / 65 µs
CIE Flux Code / CEN Flux Code	77 96 99 100 100
Type of protection	IP 20 on room side IP 20
Protection class	I
Filament test	850 °C
Impact resistance	IK04
Ambient temperature	5 °C ... + 25 °C
Conformity mark	CE

TX-MOVE

901729.002.3 | Recessed projectors



Accessories



982868.002

Mounting frame for installation in suspended ceilings.