



# MASTERCOLOUR CDM-Tm Elite Mini

## MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT

Mini, single-ended, very high-efficiency, long-life Ceramic Metal Halide discharge lamp producing crisp white sparkling light with high color rendering

### Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- For 50W use with Philips electronic gear only
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

Operating and Electrical		Color Designation	
Power Consumption	20.1 W	Color Designation	Warm White (WW)
Voltage (Nom)	95 V	Chromaticity Coordinate X (Nom)	0.434
Voltage (Nom)	95 V	Chromaticity Coordinate Y (Nom)	0.398
General Information		Correlated Color Temperature (Nom)	3000 K
Cap-Base	GU6.5 [GU6.5]	Luminous Efficacy (rated) (Nom)	90 lm/W
Operating Position	UNIVERSAL [Any or Universal (U)]	Color rendering index (CRI)	84
Flux measurement reference	Sphere	Controls and Dimming	
Light Technical		Dimmable	No
Color Code	830 [CCT of 3000K]	Mechanical and Housing	
Luminous Flux	1,800 lumen	Bulb Finish	Clear

# MASTERCLOUR CDM-Tm Elite Mini

Bulb Shape	T-4
<b>Approval and Application</b>	
Mercury (Hg) Content (Max)	3.5 mg
Mercury (Hg) Content (Nom)	3.5 mg
Energy Consumption kWh/1000 h	21 kWh
EPREL Registration Number	473,256
<b>Product Data</b>	
Full product code	872790089083900


Order product name	MC CDM-Tm Elite Mini 20W/830 GU6.5 ICT
Order code	928183505130
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	928183505130
Full product name	MC CDM-Tm Elite Mini 20W/830 GU6.5 ICT
EAN/UPC - Case	8727900890846

## Dimensional drawing

D

Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MC CDM-Tm Elite Mini 20W/830 GU6.5 ICT	13.3 mm	0.5 inch	3.4 mm	28 mm	32 mm	30 mm	56.7 mm

## Photometric data




Light Distribution Diagram - MC CDM-Tm Elite Mini 20W/830 GU6.5 ICT

Spectral Power Distribution Colour - MC CDM-Tm Elite Mini 20W/830 GU6.5 ICT

# MASTERCcolour CDM-Tm Elite Mini

## Lifetime



Life Expectancy Diagram - MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT

Lumen Maintenance Diagram - MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT

