


# Guardian Lithium Bulkhead



- Ultra-slim profile LED polycarbonate bulkhead
- Supplied with self-adhesive legend
- Self-test as standard
- 20mm side, end and rear cable entries
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Quick release LED array/gear tray assembly provides the installer the means to faster installation/maintenance
- Viewing distance 18 metres



| ***                 | Escape route 2 metres wide (1 Lux minimum) * |                          |               |                |
|---------------------|--|--------------------------|---------------|----------------|
|                     | Transverse to Wall                           | Transverse to Transverse | Axial to Wall | Axial to Axial |
| Mounting Height (M) |  |                          |               |                |
| 2.5                 | 3  | 7.5                      | 1.8           | 4.5            |
| 4                   | 3  | 7                        | 1             | 3.5            |
| -                   | -  | -                        | -             | -              |

| ***                 | Open (Anti-Panic) area (0.5 Lux Minimum) ** |                          |               |                |
|---------------------|---|--------------------------|---------------|----------------|
|                     | Transverse to Wall                          | Transverse to Transverse | Axial to Wall | Axial to Axial |
| Mounting Height (M) |   |                          |               |                |
| 2.5                 | 3   | 6.5                      | 3             | 6.5            |
| 4                   | 3   | 7.5                      | 3             | 7.5            |
| 6                   | 2.5   | 8                        | 2.5           | 8              |

| INPUT    | HERTZ | TEMP        | LIFETIME (HRS) | BEAM ANGLE | CLASS | IP   | IK   |
|----------|-------|-------------|----------------|------------|-------|------|------|
| 220/240V | 50Hz  | 5°C to 40°C | L70 54,000     | 130°       | 2     | IP65 | IK08 |

| CODE     | DESCRIPTION                            | WATTAGE | CCT   | STANDARD MODE | EMERGENCY MODE | TRADE  |
|----------|--|---------|-------|---------------|----------------|--------|
| AGLED/3M | Daylight - Maintained / Non-Maintained | 3W      | 6500K | 173m          | 167m           | £38.20 |

| CODE (ACCESSORIES) | DESCRIPTION                              | TRADE  |
|--------------------|--|--------|
| AGLED/KIT          | Semi-Recessing Kit                       | £15.00 |
| ASBP/30/LI         | 3.2V 1500mAh LiFePO4 Replacement Battery | £7.40  |