

# MASTER Value GLASS LED candles and lusters

## MAS VLE LEDCandleD3.4-40W E14 B35 927CLG

MASTER Value Glass LED lusters features a classic heritage design, these filament LED lamps combine the familiar shapes of incandescent candles and lusters with the benefits of long-lasting LED technology. These glass LED lusters offer more energy savings than normal LED candles and lusters. At the same time, they also provide customers with a good light experience, enhanced by excellent dimming performance (dimmable LED candles). MASTER Value Glass LED lusters and lusters deliver significant energy savings, using 30% less energy compared to normal glass LED candles and provide excellent quality of light. By offering a lifetime of 15,000 hours these dimmable LED candles and lusters also reduce maintenance costs.

### Product data

General Information	
Cap-Base	E14
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	927 [CCT of 2700K]
Luminous Flux	470 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	138.00 lm/W

Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RGO
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	3.4 W
Lamp Current (Nom)	20 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s

# MSTER Value GLASS LED candles and lusters

Power Factor (Fraction)	0.7
Voltage (Nom)	220-240 V
<b>Temperature</b>	
T-Case Maximum (Nom)	80 °C
<b>Controls and Dimming</b>	
Dimmable	Only with specific dimmers
<b>Mechanical and Housing</b>	
Bulb Finish	Clear
Bulb Shape	B35
Net Weight (Piece)	0.014 kg
<b>Approval and Application</b>	
Energy Efficiency Class	D
Energy Consumption kWh/1000 h	4 kWh
EPREL Registration Number	574369
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes

Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4


## Application Conditions

can it be used in closed luminaires	No
-------------------------------------	----

## Product Data



Order product name	MAS VLE LEDCandleD3.4-40W E14 B35 927CLG
Full product name	MAS VLE LEDCandleD3.4-40W E14 B35 927CLG
Full product code	871951435543900
Order code	929003059502
Material Nr. (12NC)	929003059502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514355439
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514355446

## Dimensional drawing



Product	D	C
MAS VLE LEDCandleD3.4-40W E14 B35 927CLG	35 mm	97 mm

## Photometric data




Spectral Power Distribution Colour - MAS VLE LEDCandleD3.4-40W E14 B35 927CLG

Light Distribution Diagram - MAS VLE LEDCandleD3.4-40W E14 B35 927CLG

# MSTER Value GLASS LED candles and lusters

## Photometric data



General Uniform Lighting  
1x 9270205 VLE  
Lx 2100lm  
Lx 2100lm

General uniform lighting - MAS VLE LEDCandleD3.4-40W E14 B35 927CLG

## Lifetime



Life Expectancy Diagram

Lumen Maintenance Diagram - MAS VLE LEDCandleD3.4-40W E14 B35 927CLG

