

ASTRA LED 12800LM 840 AR2 IP66 I CL. WIRE 0,7M WTYK/GN SP10KV (103W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	664816
Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	103
Luminous flux [lm]*:	12800
Colour temperature [K]:	4000
SDCM:	≤ 5
Colour rendering index:	> 80
Electrical protection class:	I
Energy efficiency class:	D

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 153 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (GF) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN-EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom). Options: any RAL color. RCR sensor controlled by remote control.

APPLICATION

Luminaire applicable to: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.

ASTRA LED 12800LM 840 AR2 IP66 I CL. WIRE 0,7M


WTYK/GN SP10KV (103W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	664816	Impact resistance:	IK08
EAN:	6648165905963	Ingress protection:	IP66
Rated power of the luminaire [W]:	103	Mounting version:	Top, on pole / Side, on boom
Light source:	LED module	Working temperature [°C]:	from -20 to +35
Colour temperature [K]:	4000	Tilt angle adjustment [°]:	-5 to +15 (peak); -15 to +5 (side)
Luminous flux [lm]:	12800	Lateral surface (SCx) [m2]:	0.018
Supply voltage [V]:	220 - 240	Wire type:	H07RN-F
Frequency [Hz]:	50 - 60	Cable length [m]:	0.70
Optics:	AR2	Protection type:	10kV
Luminous efficacy [lm/W]:	125	Number on the palette [pcs]:	62
Energy efficiency class:	D	Net weight [kg]:	1.900
Electrical protection class:	I	Category type:	street lighting
Colour rendering index:	> 80	LED lifespan L80B20 [h]:	71000
SDCM:	≤ 5	ETIM class:	EC000062
Power factor:	0.98	Surge protection [kV]:	10
Diffuser material:	PC	ULOR:	0%
Diffuser type:	matrix led	Control:	ON/OFF
Diffuser colour:	transparent	Optics material:	PC
Material of the body:	PP+FG	Warranty [years]:	5
Colour of the body:	gray	CE certificate:	104/2023
Dimensions (H/W/T/S) [mm]:	640/233/113	ENEC Certificate:	0323/ENEC/23
Mounting dimensions [mm]:	ø60	Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES



ASTRA LED 12800LM 840 AR2 IP66 I CL. WIRE 0,7M WTYK/GN SP10KV (103W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00229	mounting grip 78 mm



wall holder (galvanized) (314049)



wall holder (grey) (314056)



mounting grip 78 mm (UL00229)

Card creation date: 03 June 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 104/2023