


SQ 600 LED 3700LM PLX DALI I KL. IP20 592X592MM 840 (37W) RAL9005

DETAILED CARD



TECHNICAL PARAMETERS

Index:	668227
Ingress protection:	IP44/IP20
Nominal power [W]:	37
Luminous flux [lm]*:	3700
Colour rendering index:	>80
SDCM:	≤ 5
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

CHARACTERISTICS

SQ 600 LED is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

The luminaire is available in 2 versions:

- with OPAL diffuser - providing soft light;
- with PRM diffuser - with higher luminous efficiency and low glare UGR <19 (18W, 24W, 32W versions).

Available options:

- RCR sensor - sensor used for motion detection, without twilight detection option; uses microwaves for detection (active sensor),
- control in the DALI standard,
- CORRIDOR corridor function (RCR + DALI).

The ingress protection- depends on the method of installation:

- surface mounted - IP20,
- flush-mounted - IP44/20.

APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


SQ 600 LED 3700LM PLX DALI I KL. IP20 592X592MM 840 (37W) RAL9005

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	37	Optics:	lens
Index:	668227	Material of the body:	ABS
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	592/592/44
Light source:	LED module	Mounting dimensions [mm]:	563/297
Luminous flux [lm]:	3700	Ingress protection:	IP44/IP20
Diffuser type:	OPAL	Glow wire test [°C]:	650
Rated power of the luminaire [W]:	42.40	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Supply voltage [V]:	220-240	Net weight [kg]:	2
Frequency [Hz]:	50 - 60	Category type:	louvres
DIMM DALI:	yes	Category of application:	commercial facilities, educational institutions
Colour of the body:	black mat	AC voltage range [V]:	198 - 264
Luminous efficacy [lm/W]:	87	DC voltage range [V]:	176-280
Energy efficiency class:	F	LED lifespan L70B50 [h]:	50000
Electrical protection class:	I	LED lifespan L80B20 [h]:	32000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	15000
SDCM:	≤ 5	Light distribution type:	open space
Power factor:	0.96	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Diffuser material:	PS	Technical Warranty:	5
Diffuser colour:	white	PZH certificate:	B-BK-60212-0618/20
Optics material:	PMMA	CE certificate:	110/2023
		Manual:	Download PDF
		ENEC Certificate:	PL BBJ/006/2021/M1
		Plik LDT:	Download

LIGHT CURVES



SQ 600 LED 3700LM PLX DALI I KL. IP20 592X592MM 840 (37W) RAL9005

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
978395	Installation kit SQ 600 Ceiling system H40 100x100
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 110/2023