

PRODUCT DATASHEET DP HOUSING 1200 P 2XLAMP IP65

DAMP PROOF HOUSING GEN 3 | Damp-proof luminaire for T8 LED lamps with tool-free luminaire connector



Areas of application

- Parking lots, warehouses, production areas
- Car parks and underpasses
- Garages



Product benefits

- Easy and quick installation
- Prewired for easy installation of tubular AC LED lamps
- Toolless installation
- Robust housing
- Sustainable solution thanks to exchangeable light sources
- 5 years guarantee

Product features

- Luminaire housing, available for 1 or 2 T8 LED tubes
- Suitable for LED TUBE T8 EM and LED TUBE T8 CONNECTED
- Type of protection: IP65
- Integrated electrical fuse




TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	П

Dimensions & Weight

Length	1280.00 mm
Width	95.00 mm
Height	70.00 mm
Product weight	899.00 g



DP HOUSING 1200 P 2XLAMP IP65

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30+40 °C
Temperature range at storage	-20+80 °C

Type of connection Screwless terminal, 3-Pole (N, E, L)	
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	No
Holder designation	G13

Certificates & Standards

Standards	CE / TÜV Rheinland / EAC / UKCA	
Luminaire with limited surface temperature, "D sign"	No	
Ball shot safe	No	

Accessories Optional

Product image	Product name	EAN
Q	DP HOUSING 1200 2xLAMP TH-KIT 5x2.5	4058075695115

EQUIPMENT / ACCESSORIES

- All required accessories included
- Through-wiring cable kit available

DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	DP HOUSING
PDF	Legal information	LI DP HOUSING
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
POF	Declarations of conformity	DP HOUSING


	Documents and certificates	Document name	
POF	Declarations of conformity UKC	KCA DP HOUSING	
	Photometric and lighting design	n files Document name	
	IES file (IES)	DP HOUSING 1200 P 2xL IP65 incl LEDTUBE CON P 16W	
	LDT file (Eulumdat)	DP HOUSING 1200 P 2xL IP65 incl LEDTUBE CON P 16W	
	ULD file (DIALux)	DP HOUSING 1200 P 2XLAMP IP65	
	CAD/BIM files	Document name	
	BIM Revit 3D	Damp Proof Housing G3	
	CAD STEP 3D	DP HOUSING G3 2 1200	
	Tender texts	Document name	
	Tender documents	DAMP PROOF HOUSING GEN 3 1200 P 2XLAMP IP65-EN	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854118111	Folding box 1	98 mm x 1,272 mm x 75 mm	1059.00 g	9.35 dm ³
4099854118128	Shipping box 9	1,287 mm x 306 mm x 237 mm	10231.00 g	93.34 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.