


Lodi Slim Downlight



- Economic circular LED performance downlight suitable for semi-commercial and residential applications
- Low profile design with integral driver
- Ideal for use in areas with shallow ceiling voids
- Supplied pre-wired with 300mm of cable



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220 - 240V	50Hz	-15°C to 25°C	L70 25,000	Ra 80	6	115°	2	IP20

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR	A	B	TRADE
ALODLED/75/CW		4W		410lm	103lm		90mm	75mm	£7.30
ALODLED/95/CW	Cool White	8W	4000K	810lm	101lm	30	115mm	100mm	£8.50
ALODLED/110/CW		12W		1280lm	107lm		140mm	125mm	£9.70
ALODLED/75/WW		4W		390lm	98lm		95mm	75mm	£7.30
ALODLED/95/WW	Warm White	8W	3000K	760lm	95lm	30	120mm	100mm	£8.50
ALODLED/110/WW		12W		1200lm	100lm		140mm	125mm	£9.70

* UGR Value based on (4H - 8H)

CODE (ACCESSORIES)	DESCRIPTION	TRADE
ASLED/3NM	1.5W Non-Maintained	£49.55