

CORIA 2 4700LM 600MM I CL. IP40 BLACK MAT 830 50W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	275661
Ingress protection:	IP40
Rated power [W] - range:	50
Luminous flux of the luminaire [lm] - range:	4700
Colour temperature [K]:	3000
Colour rendering index:	>80
Electrical protection class:	I
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

The Coria 2 LED circular luminaire with integrated energy-efficient LED module is characterised by its high luminous efficacy and uniform light distribution. Its base is made of white or black powder-coated aluminium and its diffuser is made of microprism (300mm diameter version only) or opal plastic. It is ideal for new applications and for replacing traditional fluorescent lamps with energy-efficient LED solutions. Characteristics: colour temperature 3000K, 4000K; CRI>80; LED module life 119,000 hours (L80B20) ta = 25°C; pendant or surface-mounted version.

APPLICATION

The luminaire is designed for indoor use. It is characterised by even light distribution and good surface illumination, which is why it is particularly dedicated as a source of general light in representative rooms and passageways. Thanks to its excellent luminous parameters, the luminaire is ideal for large conference rooms. The luminaire's construction has been adapted for surface-mounted or flush-mounted installation in plasterboard ceilings. Revit files for architectural luminaires are available on request.

CORIA 2 4700LM 600MM I CL. IP40 BLACK MAT 830 50W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	275661	Ingress protection:	IP40
EAN:	5905963275661	Mounting version:	surface
Light source:	LED	Working temperature [°C]:	from -10 to +35
Rated power [W] - range:	50	Dimensions of single box [mm]:	675
Colour temperature [K]:	3000	Number on the palette [pcs]:	12
Luminous flux of the luminaire [lm] - range:	4700	Net weight [kg]:	4.900
Diffuser type:	OPAL	Category type:	bulkheads
Luminous efficacy [lm/W]:	94	LED lifespan L70B50 [h]:	189000
Energy efficiency class:	E	LED lifespan L80B20 [h]:	119000
Electrical protection class:	I	LED lifespan L90B10 [h]:	57000
Colour rendering index:	>80	Light distribution type:	lambertian
Diffuser material:	PC	SDCM:	≤ 3
Colour of the body:	black	Warranty [years]:	5
Material of the body:	aluminium	CE certificate:	04/2024
Dimensions (H/W/T/S) [mm]:	600/86	Manual:	Download PDF
Mounting dimensions [mm]:	500	Plik LDT:	Download

LIGHT CURVES

