



Ledinaire panel gen5

RC065B G5 34_36S/830_40 PSU 30x120 OC SC

Ledinaire panel gen5, All-in, 28 W, 1200x300 mm, VPC, 3400 lm, 3600 lm, 3000 K, 4000 K, UGR19

The Philips Ledinaire panel Gen5 (RC065B/RC066B) range features a selection of popular off-the-shelf LED luminaires that offer Philips high quality at a competitive price. Reliable, energy-efficient and affordable, this latest generation of 600 x 600 mm, 620 x 620 mm, 300 x 1200 mm, and 600 x 1200 Ledinaire LED panel lights are designed for diffuse, comfortable lighting in a wide range of general lighting applications. Our range of Ledinaire panels lighting is also available with accessories for easy installation on different types of ceilings—just what you need.

Product data

General Information		Unified glare rating CEN	
Number of gear units	1 unit		19
Driver included	Yes	All-in Type	All-in, Multi Color Temperature
Value ladder	Value	Operating and Electrical	
Warranty period	3 years	Input Voltage	220 to 240 V
Sustainability rating	-	Line Frequency	50 or 60 Hz
Light Technical		Inrush current	16 A
Luminous Flux	3,400 3,600 lm	Inrush time	0.2 ms
Correlated Color Temperature (Nom)	3000 4000 K	Power Consumption	28 W
Luminous Efficacy (rated) (Nom)	120 lm/W	Power Factor (Fraction)	0.9
Color rendering index (CRI)	>80	Connection	Push-in connector 2-pole
Beam angle of light source	90 degree(s)	Cable	-
Light source color	3000K/3500K/4000K	Number of products on MCB of 16 A type B	20
Optic type	Beam angle 90°	Suitable for random switching	Not applicable
Luminaire light beam spread	90°	Protection class IEC	Safety class II

Ledinaire panel gen5

Total harmonic distortion	20 %
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit external (On/Off)
Control interface	-
Constant light output	No
Maximum dim level	Not applicable
Mechanical and Housing	
Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover material	Acrylate
Fixation material	-
Housing Color	White
Optical cover finish	Microprismatic lens
Overall length	1,195 mm
Overall width	295 mm
Overall height	60 mm
Dimensions (Height x Width x Depth)	60 x 295 x 1195 mm
Compatible ceiling or ceiling installation accessory type	Visible profile ceiling version
Ingress protection code	IP20/40 [Finger-protected;Wire-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Safety device	SC [Safety cable]
Net Weight (Piece)	1.750 kg
Emergency Operation	
Central Emergency	No
Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 0 @200mm to EN62778

Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Ambient temperature range	-10 to +35 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.43, 0.40) SDCM ≤5(0.38, 0.38) SDCM ≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L80
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	-
Product Data	
Order product name	RC065B G5 34_36S/830_40 PSU 30x120 OC SC
Full product name	RC065B G5 34_36S/830_40 PSU 30x120 OC SC
Full product code	872016951698499
Order code	911401877585
Material Nr. (12NC)	911401877585
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169516984
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169517004

Ledinaire panel gen5

Dimensional drawing

