

LINE

WALL LIGHT | PATH-LIGHT

STH9725BR/30



6W

Power

40lm

Luminous flux

4°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Beam angle	4°
Luminous efficacy	7lm/W
Power factor	0,92
Luminous flux	40lm
Frequency	50/60Hz
Ingress protection rating (IP)	IP65
CRI (Color rendering index)	80
Luminous intensity	450cd
Power	6W
Correlated color temperature (CCT)	3000K
Operation temperature	-20°C ~ 60°C
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h

Technical Drawing

STH9725




Graphics

STH9725BR

1m	584lx	0,2m
2m	146lx	0,4m
3m	65lx	0,5m
4m	37lx	0,7m
5m	23lx	0,9m

h, Emax, Ø

STH9725BR



OTHER INFORMATION

Finishing	White
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Aluminum

DOWNLOADS

↓ IES FILE - STH9725BR/30

↓ MANUAL Line

↓ SKETCHUP - STELLA - STH9725BR-30 - STH9725PTO-30 - LINE_PACK.zip

↓ REVIT - STH9725BR_30_STH9725PTO_30_Balizador.rfa

