

SQ 160 LED P 2750LM 75DEG 830 (21W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	570896
Ingress protection:	IP44/20
Nominal power [W]:	21
Luminous flux [lm]*:	2750
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	D
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PS

CHARACTERISTICS

SQ 160 LED P is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


SQ 160 LED P 2750LM 75DEG 830 (21W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	21	Dimensions (H/W/T/S) [mm]:	158/158/70
Index:	570896	Mounting dimensions [mm]:	145x145
Colour temperature [K]:	3000	Impact resistance:	IK08
Light source:	LED module	Ingress protection:	IP44/20
Luminous flux [lm]:	2750	Glow wire test [°C]:	650
Diffuser type:	OPAL	Mounting version:	recessed
Rated power of the luminaire [W]:	22	Working temperature [°C]:	from -20 to +35
Beam angle [°]:	75	Net weight [kg]:	0.270
Supply voltage [V]:	220 - 240	Warranty [years]:	5
Energy efficiency class:	D	Category type:	downlights
Frequency [Hz]:	50 - 60	LED lifespan L70B50 [h]:	132000
Luminous efficacy [lm/W]:	125	LED lifespan L80B20 [h]:	84000
Electrical protection class:	I	LED lifespan L90B10 [h]:	42000
Colour rendering index:	>80	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.99	Category of application:	HoReCa, commercial facilities, educational institutions, art and culture
Diffuser material:	PS	Manual:	Download PDF
Optics:	lens	CE certificate:	315/2023
Material of the body:	ABS	Pliik LDT:	Download
Colour of the body:	white		

LIGHT CURVES



SQ 160 LED P 2750LM 75DEG 830 (21W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
998942	Frame square 220 for SQ160 white RAL9016 structure



Frame square 220 for SQ160 white
RAL9016 structure (998942)

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 315/2023