
## Otto Evo CCT Bi-directional Suspended Linear







- Architectural suspended linear for office, retail and educational applications
- Slim profile available in white, aluminium and black finishes
- Adjustable bracket system allows complete flexibility for mounting installation
- Specially designed diffuser allows installer quick access to wiring ensuring a quick and easy installation
- Selectable CCT between 3000K and 4000K output
- Supplied bi-directional light output as standard (directional only option can be selected if required)
- Suitable for individual or continuous suspension
- Die-Cast aluminium end caps
- Supplied c/w 1.5m suspension kit as standard









Black



Available
Powered by
CASAMBI

AOTEVLED5 fitted with AOTEVLED/90 90° Corner Connector

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220-240V	50/60Hz	0°C to 25°C	L90 60,000	Ra 80	3	110°	1	IP20

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR	TRADE
AOTEVLED5	1 x 1500mm - Aluminium	42W	20001//40001/	4170lm (4000K)	99lm (4000K)	23	£276.00
AOTEVLED2X5	2 x 1500mm - Aluminium	66W	3000K/4000K	8030lm (4000K)	122lm (4000K)	25	£307.00

For white or black variant add 'W' or 'B' into the above product codes e.g. **AOTEVLED5/W** or **AOTEVLED5/B** 

White

\* UGR Value based on (4H - 8H)

_			
ı	CODE (OPTIONS)	DESCRIPTION	TRADE
	/M3	Emergency	+ £90.00
	/DM3	DALI Emergency	+ £205.00
	/DD	Digital Dimming (DD1/DD3/DD4)	+ £95.00

CODE (ACCESSORIES)	DESCRIPTION	TRADE
AOTEVLED500	500mm Infill - Aluminium	£86.50
AOTEVLED1000	1000mm Infill - Aluminium	£130.00
AOTEVLED1500	1500mm Infill - Aluminium	£178.00

CODE (OPTIONS)	DESCRIPTION	TRADE
/MWS	Integral Microwave Sensor	+ £60.00
/CF	Corridor Function	+ £130.00
/OCTO	OCTO Smart Control	+ £195.00

CODE (ACCESSORIES)	DESCRIPTION	TRADE
AOTEVLED/90	90° Corner Connector - Aluminium	£29.15
AOTEVLED/90/W	90° Corner Connector - White	£29.15

For white or black variant add 'W' or 'B' into the above product codes e.g. **AOTEVLED500/W** or **AOTEVLED500/B** 

