

## WALL MINI

WALL-MOUNTED EFFECT LIGHT | 1 WIDE BEAM |  
1 NARROW BEAM

STH9731BR/30



5W

Power

110lm  
(100lm/10lm)lm

Luminous flux


70° / 4°

Beam angle


### TECHNICAL SPECIFICATIONS TABLE

|                                    |                    |
|------------------------------------|--------------------|
| Beam angle                         | 70° / 4°           |
| Power factor                       | 0,92               |
| Luminous flux                      | 110lm (100lm/10lm) |
| Frequency                          | 50/60Hz            |
| Ingress protection rating (IP)     | IP65               |
| CRI (Color rendering index)        | 80                 |
| Power                              | 5W                 |
| Correlated color temperature (CCT) | 3000K              |
| Operation temperature              | -10°C ~ 40°C       |
| Voltage (V)                        | 100-240V           |
| Voltage (Vac)                      | 100-240Vac         |
| Lifespan                           | 25000h             |

### Technical Drawing



### Graphics



### OTHER INFORMATION

|                     |                  |
|---------------------|------------------|
| Finishing           | White            |
| Color temperature   | Warm white       |
| Dimmable            | No               |
| Warranty            | 2 years          |
| Patent information  | Patented product |
| Prevailing material | Polycarbonate    |

### DOWNLOADS

MANUAL Wall Mini

SKETCHUP - STELLA - STH9731BR-30 - STH9731PTO-30 - WALL MINI - FACHO ABERTO\_PACK.zip

REVIT - STH9731BR\_30\_STH9731PTO\_30.rfa

