

# TIUNNE PLUS 200 3250LM 830 DALI 15D BLACK IP65/IP20 REFLECTOR B 36W

---

DETAILED CARD



# TIUNNE PLUS 200 3250LM 830 DALI 15D BLACK IP65/IP20 REFLECTOR B 36W

## DETAILED CARD

### TECHNICAL PARAMETERS

|                                           |           |
|-------------------------------------------|-----------|
| <b>Index:</b>                             | 921759    |
| <b>Ingress protection:</b>                | IP65/IP20 |
| <b>Rated power of the luminaire [W]*:</b> | 36        |
| <b>Luminous flux [lm]*:</b>               | 3250      |
| <b>Colour temperature [K]:</b>            | 3000      |
| <b>Colour rendering index:</b>            | >80       |
| <b>Energy efficiency class:</b>           | F         |
| <b>Material of the body:</b>              | aluminium |
| <b>Colour of the body:</b>                | white     |
| <b>Diffuser material:</b>                 | PC        |

### CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

### APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

### DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h

### DETAILED CARD

|                                          |               |
|------------------------------------------|---------------|
| <b>Rated power of the luminaire [W]:</b> | 36            |
| <b>Index:</b>                            | 921759        |
| <b>Colour temperature [K]:</b>           | 3000          |
| <b>EAN:</b>                              | 5905963921759 |
| <b>Luminous flux [lm]:</b>               | 3250          |
| <b>Light source:</b>                     | COB           |
| <b>Remarks:</b>                          | B- black matt |
| <b>Luminous efficacy [lm/W]:</b>         | 91            |
| <b>Energy efficiency class:</b>          | F             |
| <b>Colour rendering index:</b>           | >80           |
| <b>Electrical protection class:</b>      | II            |
| <b>Beam angle [°]:</b>                   | 15            |
| <b>SDCM:</b>                             | 3             |
| <b>Surge protection [kV]:</b>            | 1             |
| <b>Optics:</b>                           | reflector B   |
| <b>Diffuser material:</b>                | PC            |
| <b>Diffuser type:</b>                    | transparent   |
| <b>Optics material:</b>                  | aluminium     |

|                                   |                              |
|-----------------------------------|------------------------------|
| <b>Ring colour:</b>               | black                        |
| <b>Material of the body:</b>      | aluminium                    |
| <b>Dimensions (H/W/T/S) [mm]:</b> | ø215/110                     |
| <b>Colour of the body:</b>        | white                        |
| <b>Ring material:</b>             | aluminium                    |
| <b>Mounting dimensions [mm]:</b>  | 200                          |
| <b>Ingress protection:</b>        | IP65/IP20                    |
| <b>DIMM DALI:</b>                 | yes                          |
| <b>Impact resistance:</b>         | IK08                         |
| <b>Mounting version:</b>          | recessed                     |
| <b>Working temperature [°C]:</b>  | 35                           |
| <b>Net weight [kg]:</b>           | 0.550                        |
| <b>Category type:</b>             | downlights                   |
| <b>Warranty [years]:</b>          | 5                            |
| <b>CE certificate:</b>            | <a href="#">469/2023</a>     |
| <b>Manual:</b>                    | <a href="#">Download PDF</a> |
| <b>Plik LDT:</b>                  | <a href="#">Download</a>     |

# TIUNNE PLUS 200 3250LM 830 DALI 15D BLACK IP65/IP20 REFLECTOR B 36W

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name                                                |
|--------|-----------------------------------------------------|
| 416835 | Masking ring 198/257 Tiunne Plus 200 RAL9016        |
| 416859 | Masking ring 198/257 Square Tiunne Plus 200 RAL9016 |