



Pole top luminaires  
4051859678953  
D 187, H 572

Pole mounting  
anthracite metallic (DB703)



Pole-top luminaire with classic design and modern LED technology. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. With stainless steel screws. With membrane valve as a standard to avoid condensed water. Diffuser: glass, transparent. Multi-chip LED with high-performance refractor optics. Symmetrical light distribution Pole attachment for 76 mm spigot. With stainless steel screws. Elegant-looking power supply via delicate steel cables between converter and LED. Converter integrated in the luminaire head. 4 x 1.0 mm² connecting cable included, length 5.5 m. Please order reducer adapter for pole clamp D 60 mm separately. Order the top roof separately as an accessory for the classic lantern shape.

Product specifications

|                                              |                          |
|----------------------------------------------|--------------------------|
| Diameter D                                   | 187 mm                   |
| Height H                                     | 572 mm                   |
| Weight                                       | 6.1 kg                   |
| Light source                                 | LED                      |
| Colour temperature                           | 3000 K                   |
| Rated luminous flux                          | 1750 lm                  |
| System power                                 | 14 W                     |
| System efficiency                            | 125 lm/W                 |
| Glare evaluation UGR (4H 8H)                 | 26                       |
| Beam angle                                   | 153°/153°                |
| Rated life                                   | 100000 h (L80/B10)       |
| Colour rendering index (CRI)                 | 70                       |
| Colour tolerance                             | 5                        |
| Photobiological safety according to EN 62471 | Risk group 2             |
| Driver                                       | Converter, dimmable      |
| Control                                      | DALI                     |
| Voltage                                      | 220 - 240 V / 50 - 60 Hz |
| Luminaires on B10A fuse                      | 18                       |
| Luminaires on B16A fuse                      | 28                       |
| Inrush current / Inrush current duration     | 26 A / 180 µs            |
| CIE Flux Code / CEN Flux Code                | 15 45 92 100 100         |
| Type of protection                           | IP 66                    |
| Protection class                             | II                       |
| Filament test                                | 960°C - 30 seconds       |
| Impact resistance                            | IK06                     |
| Ambient temperature                          | -20 °C ... + 40 °C       |
| Conformity mark                              | CE, EAC                  |

Accessories



982752.0031  
Top roof



982762.000  
Reducing adapter Ø 60 mm