



CorePro GLASS LED candles and lusters

CorePro LEDCandleND6.5-60WB35 E14 840FRG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information		Photobiological safety according to EN 62471	
Cap-Base	E14		RG1
Nominal lifetime	15,000 hour(s)		
Switching Cycle	20,000		
Lighting Technology	LED		
Flux measurement reference	Sphere		
Light Technical		Operating and Electrical	
Color Code	840 [CCT of 4000K]	Line Frequency	50 to 60 Hz
Luminous Flux	806 lm	Input Frequency	50 to 60 Hz
Color Designation	Cool White (CW)	Power Consumption	6.5 W
Correlated Color Temperature (Nom)	4000 K	Lamp Current (Nom)	50 mA
Luminous Efficacy (rated) (Nom)	124.00 lm/W	Wattage Equivalent	60 W
Color Consistency	<6	Starting Time (Nom)	0.5 s
Color rendering index (CRI)	80	Warm-up time to 60% light	0.5 s
LLMF At End Of Nominal Lifetime (Nom)	70 %	Power Factor (Fraction)	0.55
		Voltage (Nom)	220-240 V
		Temperature	
		T-Case Maximum (Nom)	55 °C

CorePro GLASS LED candles and lusters

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Frosted
Bulb Shape	B35
Net Weight (Piece)	0.012 kg

Approval and Application

Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	1825176
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.9


Application Conditions

can it be used in closed luminaires	No
-------------------------------------	----

Product Data



Order product name	CorePro LEDCandleND6.5-60WB35 E14 840FRG
Full product name	CorePro LEDCandleND6.5-60WB35 E14 840FRG
Full product code	871951434752600
Order code	929002028392
Material Nr. (12NC)	929002028392
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514347526
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514347533

Dimensional drawing



Product	D	C
CorePro LEDCandleND6.5-60WB35 E14 840FRG	35 mm	97 mm

Photometric data




General uniform lighting - CorePro LEDCandleND6.5-60WB35 E14 840FRG

Spectral Power Distribution Colour - CorePro LEDCandleND6.5-60WB35 E14 840FRG


CorePro GLASS LED candles and lusters

Photometric data




Light Distribution Diagram - CorePro LEDCandleND6.5-60WB35 E14 840FRG

Lifetime



Lumen Maintenance Diagram - CorePro LEDCandleND6.5-60WB35 E14 840FRG



Life Expectancy Diagram

