



# MASTER Value Glass LED bulbs



## MAS VLE LEDBulb D5.9-60W E27 927 A60 FRG

Featuring a classic heritage design, these filament LED bulbs combine the familiar shapes of incandescent bulbs with the benefits of long-lasting LED technology. These MASTER Value Glass LED bulbs offer more energy savings than normal glass LED bulbs. At the same time, they also provide customers with good light experience, enhanced by excellent dimming performance (dimmable glass LED bulbs). MASTER Value Glass LED Bulbs deliver significant energy savings, using 30% less energy compared to normal LED bulbs and provide excellent quality of light. By offering a lifetime of 15,000 hours, these dimmable LED bulbs also reduce maintenance costs.

### Product data


General Information		LLMF At End Of Nominal Lifetime (Nom)	
Cap-Base	E27		70 %
Nominal lifetime	15,000 hour(s)	Photobiological safety according to EN 62471	RG0
Switching Cycle	20,000	<b>Operating and Electrical</b>	
Lighting Technology	LED	Line Frequency	50 to 60 Hz
Flux measurement reference	Sphere	Input Frequency	50 to 60 Hz
<b>Light Technical</b>		Power Consumption	5.9 W
Color Code	927 [CCT of 2700K]	Lamp Current (Nom)	35 mA
Beam Angle (Nom)	300 degree(s)	Wattage Equivalent	60 W
Luminous Flux	806 lm	Starting Time (Nom)	0.5 s
Color Designation	Warm White (WW)	Warm-up time to 60% light	0.5 s
Correlated Color Temperature (Nom)	2700 K	Power Factor (Fraction)	0.7
Luminous Efficacy (rated) (Nom)	136.00 lm/W	Voltage (Nom)	220-240 V
Color Consistency	<6		
Color rendering index (CRI)	90		

# MASTER Value Glass LED bulbs

Temperature	
T-Case Maximum (Nom)	80 °C
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	A60
Net Weight (Piece)	0.030 kg
Approval and Application	
Energy Efficiency Class	D
Energy Consumption kWh/1000 h	6 kWh
EPREL Registration Number	574362
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1



Stroboscopic effect visibility measure (SVM)	0.4
Application Conditions	
can it be used in closed luminaires	No
Product Data	
Order product name	MAS VLE LEDBulb D5.9-60W E27 927 A60 FRG
Full product name	MAS VLE LEDBulb D5.9-60W E27 927 A60 FRG
Full product code	871951434786100
Order code	929003057702
Material Nr. (12NC)	929003057702
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514347861
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514347878

## Dimensional drawing



Product	D	C
MAS VLE LEDBulb D5.9-60W E27 927 A60 FRG	60 mm	104 mm

## Photometric data




General uniform lighting - MAS VLE LEDBulb D5.9-60W E27 927 A60 FRG

Light Distribution Diagram - MAS VLE LEDBulb D5.9-60W E27 927 A60 FRG

# MASTER Value Glass LED bulbs

## Photometric data




Spectral Power Distribution Colour - MAS VLE LEDBulb D5.9-60W E27 927 A60 FRG

## Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MAS VLE LEDBulb D5.9-60W E27 927 A60 FRG

