

# TIUNNE PLUS 90 730LM 840 20D WHITE IP65/IP20 REFLECTOR S 8W

---

DETAILED CARD



# TIUNNE PLUS 90 730LM 840 20D WHITE IP65/IP20 REFLECTOR S 8W

## DETAILED CARD

### TECHNICAL PARAMETERS

|                                           |           |
|-------------------------------------------|-----------|
| <b>Index:</b>                             | 416101    |
| <b>Ingress protection:</b>                | IP65/IP20 |
| <b>Rated power of the luminaire [W]*:</b> | 8         |
| <b>Luminous flux [lm]*:</b>               | 730       |
| <b>Colour temperature [K]:</b>            | 4000      |
| <b>Colour rendering index:</b>            | >80       |
| <b>Energy efficiency class:</b>           | F         |
| <b>Material of the body:</b>              | aluminium |
| <b>Colour of the body:</b>                | white     |
| <b>Diffuser material:</b>                 | PC        |

### CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

### APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

### DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h


# TIUNNE PLUS 90 730LM 840 20D WHITE IP65/IP20 REFLECTOR S 8W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |                |                            |                              |
|-----------------------------------|----------------|----------------------------|------------------------------|
| Rated power of the luminaire [W]: | 8              | Ring colour:               | white                        |
| Index:                            | 416101         | Material of the body:      | aluminium                    |
| Colour temperature [K]:           | 4000           | Dimensions (H/W/T/S) [mm]: | ø96/73                       |
| EAN:                              | 5905963416101  | Colour of the body:        | white                        |
| Luminous flux [lm]:               | 730            | Ring material:             | aluminium                    |
| Light source:                     | COB            | Mounting dimensions [mm]:  | 88                           |
| Remarks:                          | S- silver matt | Ingress protection:        | IP65/IP20                    |
| Luminous efficacy [lm/W]:         | 92             | Mounting version:          | recessed                     |
| Energy efficiency class:          | F              | Net weight [kg]:           | 0.250                        |
| Colour rendering index:           | >80            | Category type:             | downlights                   |
| Electrical protection class:      | II             | Warranty [years]:          | 5                            |
| Beam angle [°]:                   | 15             | CE certificate:            | <a href="#">469/2023</a>     |
| Optics:                           | reflector S    | Manual:                    | <a href="#">Download PDF</a> |
| Diffuser material:                | PC             | Plik LDT:                  | <a href="#">Download</a>     |
| Diffuser type:                    | transparent    |                            |                              |
| Optics material:                  | aluminium      |                            |                              |

## LIGHT CURVES



# TIUNNE PLUS 90 730LM 840 20D WHITE IP65/IP20 REFLECTOR S 8W

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name                                                |
|--------|-----------------------------------------------------|
| 416835 | Masking ring 198/257 Tiunne Plus 200 RAL9016        |
| 416859 | Masking ring 198/257 Square Tiunne Plus 200 RAL9016 |