



Pendant luminaires
4051859948605
L 362, B 125, H 192

pendant
traffic white, matt (RAL 9016)

Rectangular pendant luminaire in classic design. For escape route identification. Housing: aluminium, with plastic corner connectors. Display panels: plastic, opal, with motifs on one side/on both sides. Aluminium pendant suspension. Electronic ballast included. Self-contained system with automatic self-test. Please indicate legend number when placing your order!

Product specifications

Type of emergency lighting	Self-contained system
Monitoring	Autotest
Battery	LiFePO4
Duration	3 h
Operating mode	maintained power mode
Viewing Distance	32 m
Length L	362 mm
Width B	125 mm
Height H	192 mm
Suspension length LP	500 mm
Weight	3.17 kg
Light source	LED
Colour temperature	4000 K
System power, mains operation	4,6 W undefined W
Colour rendering index (CRI)	70
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
CIE Flux Code / CEN Flux Code	29 57 81 65 100
Type of protection	IP 44
Protection class	I
Filament test	650 °C
Impact resistance	IK03
Ambient temperature for maintained power	0 °C ... + 25 °C
Ambient temperature for non-maintained power mode	5 °C ... + 40 °C
Conformity mark	CE, EAC