

PRODUCT DATASHEET Office Line Desk Cylinder 4.8W CCT Dimmable White

Office Line Desk Cylinder | Mobile USB-Desk luminaire with 3-step dimming and color temperature adjustment function



Areas of application

- Living areas
- Tables, Desks
- Home offices

Product benefits

- Highly versatile due to selectable CCT
- Provides cold white light for an activating and warm white light for a relaxing atmosphere
- Switching and three step dimming via a touch sensitive sensor on the luminaire base
- Can be folded and bent to 170° for maximum flexibility
- Swivable luminaire head for individual orientation of light source

Product features

- Desk luminaire in attractive design and with flexible lamp arm
- Adjustable light color: 3000 K, 4000 K, 6500 K
- Lifetime up to 25,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	4.8 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	1000 mA
Inrush current	3.0 A
Inrush current time T _{h50}	100 μs
Power factor λ	1.00
Protection class	Ш
Operating mode	Mains voltage

Photometrical data

ıminous flux 328 lm		
Total luminous flux of contained light sources	400 lm	
Luminous efficacy	68 lm/W	
Color temperature 3000 K / 4000 K / 6500 K		
Reference control setting of contained light source (Kelvin)	3000 K	
Light color (designation)	Warm White / Cool White / Cool Daylight	
Color rendering index Ra	> 80	
Standard deviation of color matching	6 sdcm	
Photobiological safety group acc. to EN62778	RG0	
Beam angle	109 °	

Dimensions & Weight

Length	135 mm
Width	180.00 mm
Height	310.00 mm
Product weight	517.00 g
Cable length	1000 mm



Materials & Colors

Product color	White	
Housing color White		
Body material Acrylonitrile butadiene styrene (ABS)		
Cover material	Polycarbonate (PC)	
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

Application & Mounting

Temperature range at storage	-20+80 °C
Type of connection	USB
Type of protection	IP20
Dimmable	Yes
Type of dimming	PWM
Mounting type	Standing
Application environment	Indoor
Adjustable	Yes
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / EAC
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark Available from January 2025
--

EQUIPMENT / ACCESSORIES

- USB charging cable (cable length: 1.0 m) included

Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

DOWNLOAD DATA

	Documents and certificates Document name		
PDF	User instruction / safety instructions	OFFICE LINE DESK CYL D BK_WT	
PDF	Legal information	Legal insert residential luminaire	
PDF	Declarations of conformity	CE Declaration Desk Cylinder	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854388446	Folding box 1	157 mm x 157 mm x 268 mm	665.00 g	6.61 dm ³
4099854388453	Shipping box	644 mm x 330 mm x 295 mm	6264.00 g	62.69 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.