

# DEECOS P maxi

911540.004.2.76 | Pendant luminaires



Pendant luminaires  
4051859881735  
D 123, H 181

pendant  
silver



Cylindrical pendant luminaire. Housing: die-cast aluminium, powder-coated. Canopy made of powder-coated sheet steel with magnetic attachment. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Best colour rendering index Ra>90. Transparent suspension cable 2 m, can be shortened. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Decorative recessed suspension set available as accessory.

### Product specifications

|                                              |                          |
|----------------------------------------------|--------------------------|
| Diameter D                                   | 123 mm                   |
| Height H                                     | 181 mm                   |
| Suspension length LP                         | 2000 mm                  |
| Weight                                       | 1.64 kg                  |
| Light source                                 | LED                      |
| Colour temperature                           | 2700 K                   |
| Rated luminous flux                          | 3500 lm                  |
| System power                                 | 35 W                     |
| System efficiency                            | 100 lm/W                 |
| Glare evaluation UGR (4H 8H)                 | 11,9                     |
| Beam angle                                   | 13°                      |
| Rated life                                   | 50000 h (L90/B10)        |
| Colour rendering index (CRI)                 | 92                       |
| Colour tolerance                             | 2                        |
| Photobiological safety according to EN 62471 | Risk group 1             |
| Driver                                       | Converter, dimmable      |
| Control                                      | DALI                     |
| Voltage                                      | 220 - 240 V / 50 - 60 Hz |
| Luminaires on B10A fuse                      | 21                       |
| Luminaires on B16A fuse                      | 34                       |
| Luminaires on C10A fuse                      | 35                       |
| Luminaires on C16A fuse                      | 57                       |
| Inrush current / Inrush current duration     | 18 A / 250 µs            |
| CIE Flux Code / CEN Flux Code                | 97 100 100 100 100       |
| Type of protection                           | IP 20                    |
| Protection class                             | I                        |
| Filament test                                | 650°C - 30 seconds       |
| Impact resistance                            | IK06                     |
| Ambient temperature                          | 25 °C                    |
| Conformity mark                              | CE, EAC                  |

## Accessories



982373.003  
Spot lens



982373.023  
Flood lens



982374.000  
Diffuser, transparent



982422.002  
White plastic ring for lens.



982372.013  
Reflector medium



982372.033  
Reflector wide flood



982649.002  
Decorative glass opal matt



982373.013  
Medium lens



982375.003  
Anti-glare honeycomb louvre



982374.010  
Diffuser, satinated



982372.003  
Reflector spot



982372.023  
Reflector flood



982420.002  
White plastic ring for reflector.



982650.002  
Decorative glass opal matt