

Cesar Amp

96701197 CESAR AMP S DWN 1L930WB RD ANT

THORN

LED 9W CESA_AMP_930	IP65	IK08			
---------------------	------	------	---	---	--


Cesar Amp

Cesar Amp a wall mounted, architectural LED luminaire for decorative facade lighting, wide beam distribution. Fixed output Remote LED driver. Class III electrical, IP65, Impact strength: IK08. Housing: die-cast aluminium, powder coated anthracite. Working ambient temperature: -20°C to +50°C. Complete with 3000K LED.


Dimensions: Ø90 x 250 mm
Luminaire input power: 8.8 W
Luminaire luminous flux: 452 lm
Luminaire efficacy: 51 lm/W
Weight: 1.81 kg



TLG_CESA_F_AMP_DWN_WB_ANT.jpg



TLG_CESA_M_AMP_S_DWN.wmf



96701197.ltd

Lamp position: STD - standard
Light Source: LED
Luminaire luminous flux*: 452 lm
Luminaire efficacy*: 51 lm/W
Colour Rendering Index min.: 90
Correlated colour temperature*: 3000 Kelvin

Chromaticity tolerance (initial MacAdam): 3
Rated useful life (B10)*:
L80 70000 h at 25 °C
Ballast: 1x LED_DRV
Luminaire input power*: 8.8 W
Dimming: FIX
LOR: 1,00 ULOR: 0,00 DLOR: 1,00

This product contains a light source of energy efficiency class F.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting