LIGHTSTREAM maxi


722289.004 | Spotlights





Spotlights 4051859957119 L 743, B 291, H 56

Pole mounting, Universal mounting system silver, matt (approx. RAL 9006)



Clever combination of spotlight and pole luminaire in one. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. Tilt angle can be adjusted and locked in 5 degree steps featuring angular scale. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass, edge printed. Cover screwed to housing. Lens system made of plastic (PMMA). Replaceable LED spot modules according to ZHAGA standards. Symmetrical light distribution. Constant light output (CLO). With NFC programming interface. Pre-assembled connection cable, length 0.5 m. Modular design: Mounting set must be ordered separately.

Product specifications

1 Todact specifications	
Length L	743 mm
Width B	291 mm
Height H	56 mm
Weight	7.9 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	36600 lm
System power	248 W
System efficiency	148 lm/W
Glare evaluation UGR (4H 8H)	23,2
Beam angle	22°
Rated life	100000 h (L90/B50)
Colour rendering index (CRI)	70
Colour tolerance	5
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	2
Luminaires on B16A fuse	4
Inrush current / Inrush current duration	124 A / 330 μs
CIE Flux Code / CEN Flux Code	84 96 99 100 100
Type of protection	IP 66
Protection class	1
Filament test	960 °C
Impact resistance	IK08
Ambient temperature	-20 °C + 40 °C
Conformity mark	CE

Accessories



61199.009 Fuse box



982638.003 Junction box H with strain relief.

LIGHTSTREAM maxi

722289.004 | Spotlights





982977.003



982588.000 Pole bracket for 2 luminaires, uncoated



982589.000 Pole bracket for 3 luminaires, uncoated



982590.000 Pole bracket for 4 luminaires, uncoated



982591.000 Wall bracket, uncoated



982562.000 Reducing adapter Ø 60 mm



982974.003



982588.004 Pole bracket for 2 luminaires, powder-coated



982589.004 Pole bracket for 3 luminaires, powder-coated



982590.004 Pole bracket for 4 luminaires, powder-coated



982591.004 Wall bracket, powder-coated



982983.000 Reducing adapter Ø 42 mm

Modules



982978.004 Pole attachment for 76 mm spigot.



983117.004 Mounting bracket