


FLAT POLYMERO

672335.002.1.89 | Combined luminaires for escape route illumination



Ceiling and wall luminaires  
4051859393641  
D 360, H 100

Ceiling mounting, Wall (surface)  
white



Decorative round surface-mounted luminaire. For escape route illumination. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for Ceiling mounting, Wall (surface). Driver integrated. Suitable for connection to central battery systems. With AC Control monitoring module for LUXIFAIR central battery units.

Product specifications


Type of emergency lighting	Central battery system
Monitoring	Luxifair AC-Control
Battery	without
Operating mode	maintained power mode
Diameter D	360 mm
Height H	100 mm
Weight	1.32 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux, mains operation	1150 lm
System power, mains operation	13 W
Rated luminous flux, emergency operation	290 lm
System power, emergency operation	3,9 W
System efficiency	88 lm/W
Glare evaluation UGR (4H 8H)	18,5
Beam angle	down 115° up 180°
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Not necessary
Control	on/off
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz
CIE Flux Code / CEN Flux Code	43 73 91 89 100
Type of protection	IP 40
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03
Ambient temperature for maintained power	-10 °C ... + 35 °C
Ambient temperature for non-maintained power mode	-10 °C ... + 35 °C
Conformity mark	CE, EAC

# FLAT POLYMERO

672335.002.1.89 | Combined luminaires for escape route illumination



## Spareparts



08-311161.012  
Replacement diffuser