

PRODUCT DATASHEET

URBAN LITE XL 150W 865 IP65 GY

URBAN LITE | Road, path and area lighting



Areas of application

- Streets
- Parking lots, city squares, parks

Product benefits

- Lightweight design
- Slim profile
- 3 years guarantee

Product features

- Asymmetric light distribution for various application areas
- Side-entry mounting for 48...60 mm poles
- Integrated 220...240 V_{AC} driver


TECHNICAL DATA

Electrical data

Nominal wattage	150.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	660 mA
Max. number of luminaires per miniature circuit breaker C16	19
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	I
Operating mode	Mains voltage

Photometrical data

Luminous flux	16200 lm
Luminous efficacy	108 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcm
Photobiological safety group acc. to EN62778	RG1
Beam angle	140 ° x 95 °




URBAN LITE XL 150W

Dimensions & Weight

Length	550.00 mm
Width	200.00 mm
Height	53.00 mm
Product weight	1540.00 g

Cable length	400 mm
--------------	--------



Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+35 °C
Type of connection	Cable, 3-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK07
Dimmable	No
Mounting type	Side entry
Mounting location	Pole
Application environment	Outdoor
With light source	Yes

Lifespan







Lifespan L70/B50 at 25 °C	35000 h ¹⁾
Number of switching cycles	20000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / REACH / RoHS
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	URBAN LIGHTING
	Legal information	URBAN LITE IP65 GY
	Legal information	URBAN LITE IP65 GY
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	URBAN LITE IP65 GY
Photometric and lighting design files		Document name
	Light distribution curve type polar	URBAN LITE XL 150W

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075678316	Folding box 1	225 mm x 58 mm x 585 mm	1865.00 g	7.63 dm ³
4058075678323	Shipping box 5	610 mm x 250 mm x 320 mm	9995.00 g	48.80 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.