



Ledinaire SlimDownlight

DN065B G4 LED20/830_840_865 19W D200 RD

Ledinaire SlimDownlight, All-in, 19 W, D200 mm, 2000 lm, 3000 K, 4000 K, 6500 K, Beam angle 110°, White, IP20/44

The LEDINAIRE range contains a selection of popular off-the-shelf LED luminaires that come with the high Philips quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need

Product data

General Information	
Light source replaceable	No
Driver included	Yes
Lighting Technology	LED
Value ladder	Value
Warranty period	3 years
Light Technical	
Luminous Flux	2,000 lm
Correlated Color Temperature (Nom)	3000 4000 6500 K
Luminous Efficacy (rated) (Nom)	105 lm/W
Color rendering index (CRI)	80
Light source color	Multi Color Temperature
Optic type	Beam angle 110°
Luminaire light beam spread	110°
Unified glare rating CEN	28
Photobiological safety according to EN 62471	RG0

All-in Type	All-in, Multi Color Temperature
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Inrush current	4.92 A
Power Consumption	19 W
Power Factor (Fraction)	0.9
Connection	Screw connection block 2-pole
Number of products on MCB of 16 A type B	55
Protection class IEC	Safety class II
Total harmonic distortion	30 %
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)

Ledinaire SlimDownlight


Constant light output	No
Mechanical and Housing	
Housing Material	Metal-Plastic
Reflector material	-
Housing Color	White
Overall length	225 mm
Overall width	225 mm
Overall height	45 mm
Overall diameter	225 mm
Dimensions (Height x Width x Depth)	45 x 225 x 225 mm
Ingress protection code	IP20/44 [Finger-protected; wire-protected, splash-proof]
Mech. impact protection code	IK03 [0.3 J]
Net Weight (Piece)	0.365 kg
Approval and Application	
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	0.7
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +40 °C

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.44, 0.403) SDCM≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5

Over Time Performance (IEC Compliant)	
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L65



Product Data	
Order product name	DN065B G4 LED20/830_840_865 19W D200 RD
Full product name	DN065B G4 LED20/830_840_865 19W D200 RD
Full product code	871951446445200
Order code	929003251432
Material Nr. (12NC)	929003251432
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514464452
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514464469

Dimensional drawing



Ledinaire SlimDownlight

Photometric data



General uniform lighting - DN065B G4 LED20/830_840_865 19W D200 RD

Light Distribution Diagram - DN065B G4 LED20/830_840_865 19W D200 RD

