


SOLANTO MULTI Z 600MM+900MM 1500-2500LM 830 IP20 I CL. OPAL BLACK 26-44W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	26 - 44
Luminous flux of the luminaire [lm] - range:	1500-2500
Colour temperature [K]:	3000
Energy efficiency class:	F
Diffuser material:	PS
Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	Ø 900/32, Ø 602/32

CHARACTERISTICS

Suspended LED luminaire composed of two rings (602 and 900mm), allowing for attractive arrangement of representative interiors. The luminaire is made of powder-coated steel in white, black, or any other color which matches the character of the interior. The diffusers made with thermoforming method emphasize the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED version allows to choose from 4 lumens and power settings increasing its versatility and functionality and at the same time reducing the number of indexes to the minimum.

APPLICATION

SOLANTO DUO is a very impressive pendant luminaire dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can also be used in flats or apartments and perfectly fits into stylish surroundings.

SOLANTO MULTI Z 600MM+900MM 1500-2500LM 830 IP20

I CL. OPAL BLACK 26-44W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	463730	Diffuser material:	PS
EAN:	5905963463730	Diffuser type:	OPAL
Light source:	LED module	Diffuser colour:	milky
Rated power [W] - range:	26 - 44	Material of the body:	Steel
Luminous flux of the luminaire [lm] - range:	1500-2500	Dimensions (H/W/T/S) [mm]:	Ø 900/32,Ø 602/32
Colour temperature [K]:	3000	Ingress protection:	IP20
Colour of the body:	black	Mounting version:	suspended
Energy efficiency class:	F	Cable length [m]:	1.20
Supply voltage [V]:	220 - 240	Number on the palette [pcs]:	1
Frequency [Hz]:	50 - 60	Net weight [kg]:	6.500
Luminous efficacy [lm/W]:	57	Warranty [years]:	5
Electrical protection class:	I	CE certificate:	219/2023
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	Manual:	Download PDF
LED lifespan L70B50 [h]:	116600	Category type:	architectural
LED lifespan L80B20 [h]:	73 600	Category of application:	HoReCa, art and culture
LED lifespan L90B10 [h]:	35700	Plik LDT:	Download