

Axyl Gild

THORN

96700471 AXYL GILD L 1W 28L 930 UWB HF ANT

LED 9W AXYL_GILD_L_UWB930 IP65 IK06  


Axyl Gild

Axyl Gild, a wall mounted, architectural LED luminaire for decorative facade lighting, with Ultra wide beam distribution. Class I electrical.. Fixed output LED driver. , IP65, Impact strength: IK06. Housing: die-cast aluminium, powder coated textured anthracite. Working ambient temperature: -20°C to +40°C. Complete with 3000K LED..


Dimensions: 265 x 100 x 110 mm
Luminaire input power: 8.7 W
Luminaire luminous flux: 782 lm
Luminaire efficacy: 90 lm/W
Weight: 2.42 kg



TLG_AXYL_F_GILD_ANT.jpg



TLG_AXYL_M_GILD_L.wmf



96700471.ltd

Lamp position: STD - standard
Light Source: LED
Luminaire luminous flux*: 782 lm
Luminaire efficacy*: 90 lm/W
Colour Rendering Index min.: 90
Correlated colour temperature*: 3000 Kelvin

Chromaticity tolerance (initial MacAdam): 3
Rated useful life (B10)*:
L80 70000 h at 25 °C
Ballast: 1x LED_DRV
Luminaire input power*: 8.7 W Power factor = 0.86
Dimming: FIX
LOR: 1,00 ULOR: 0,00 DLOR: 1,00

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting