



CorePro - LED HID SON-T



TForce Core LED road 17W 730 E27 MV

The Philips CorePro LED HID SON-T lamps offer you an easy, short-payback LED solution to replace High Intensity Discharge (HID) lamps. This new generation of products brings all the energy-efficiency and long-lifetime benefits of LED to HID replacement, while providing instant saving with a low initial investment.

Furthermore, they're designed to have the same lamp size and light distribution as other HID lamps, so you will never know the difference. All thanks to our HighPower LED filament technology. Plus, its unique IP65 design means it can be used for outdoor applications

Warnings and Safety

• Please refer to the installation guide or consult a Philips Lighting representative for the wiring diagram and instructions.

Product data

General Information	
Cap-Base	E27
Nominal lifetime	25,000 hour(s)
Switching Cycle	15,000
Lighting Technology	LED
Flux measurement reference	Sphere

Light Technical	
Color Code	730 [CCT of 3000K]
Luminous Flux	2,800 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	164.00 lm/W
Color Consistency	<6

Color rendering index (CRI)	70
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	17 W
Lamp Current (Nom)	80 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
Ballast Compatibility	Mains

CorePro - LED HID SON-T

Inrush current at mains	10.1
Max. lamp no. on MCB B type 10A - Mains	9
Max. lamp no. on MCB B type 10A - EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 10A - EM ballast with Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A - Mains	14
Max. lamp no. on MCB B type 16A - EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A - EM ballast with Compensation Capacitor.	-

Temperature

T-Case Maximum (Nom)	39.8 °C
----------------------	---------

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	T-shape
Net Weight (Piece)	0.077 kg

Approval and Application


Energy Efficiency Class	C
-------------------------	---

Energy Consumption kWh/1000 h	17 kWh
EPREL Registration Number	1641604
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	3.3
Ambient temperature range	-30 to +45 °C

Product Data

Order product name	TForce Core LED road 17W 730 E27 MV
Full product name	TForce Core LED road 17W 730 E27 MV
Full product code	871951431625600
Order code	929002484802
Material Nr. (12NC)	929002484802
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514316256
Numerator - Packs per outer box	6
EAN/UPC - Case	8719514316263

Dimensional drawing



Product	D	C
TForce Core LED road 17W 730 E27 MV	38.5 mm	168 mm

CorePro - LED HID SON-T

Photometric data

